



APC Notebook Surge Protector for AC, phone and network lines, 3 pin connection, 100-240V, EMEA
Part Number: PNOTEPROC6-EC



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Ratings and Reviews](#)

Output

Number of Outlets	1
Receptacle Style	IEC 320-C6

Input

Nominal Input Voltage	230V
Input Power	575 Watts
Input Frequency	50/60 Hz
Input Connections	IEC 320 C6
Maximum Line Current per phase	4A

Surge Protection and Filtering

Surge energy rating	600 Joules
Peak Current Normal Mode	6.50 kAmps
Peak Current Common Mode	12 kAmps
NM Surge Response Time (ns)	1 ns
Data Line Protection	RJ-11 Modem/Fax protection (two wire single line), RJ45 10/100 Base-T Ethernet protection
Let Through Voltage Rating	< 330

Physical

Net Weight	0.10 KG
Maximum Height	28.00 mm
Maximum Width	32.00 mm
Maximum Depth	110.00 mm
Shipping Weight	0.20 KG
Shipping Height	69.00 mm

Shipping Width	158.00 mm
Shipping Depth	197.00 mm
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	16.5 X 11.5 X 8.3 inches
Master Carton Weight	6.00 lbs.
Color	Silver
Units per Pallet	480.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-9000 meters

Conformance

Regulatory Approvals	A-tick, CE, CSA, FCC Part 68, GS Mark, NOM, TelePermit, UL Listed, VDE
Standard Warranty	5 years (all other countries), Lifetime (European Union countries only)
UL 1449 TVSS Rating	700V

Sustainable Offer Status

RoHS	Compliant
------	-----------