
HP Universal Adhesive Vinyl, 2 Pack





The HP Designjet printing system—the complete solution

HP Designjet and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



With Original HP 771 Vivid Photo Inks and Original HP 91 Photo Inks. Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhem Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/printpermanence.

Quality prints for day-to-day production

Offer a range of indoor and outdoor displays

Produce quality color for your day-to-day production needs. Eye-catching displays—with a permanent, pressure-sensitive adhesive—are ideal for both indoor and outdoor applications.

See application and finishing versatility

Designed for a variety of applications and finishing techniques, HP Universal Adhesive Vinyl is a highly versatile media compatible with a variety of laminates to meet a wide range of application needs. See over 75 years indoor display permanence¹.

Enjoy quick post-print processing

Gain efficiency. ICC profiles help you get the color you need quickly. Fast dry time helps keep your workflow moving.

Target customers	Applications	Benefits	
Advertising agencies	Indoor and outdoor	Outstanding image quality for day-to-day production	
Graphic artists	POP and retail displays	Fast dry time	
Sign shops	Banners	75+ years unlaminated indoor display permanenc on HP Designjet Z-series printers¹	
Print service providers		Designed for a range of applications and finishing methods	

Technical specifications



HP Universal Adhesive Vinyl, 2 Pack

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format materials, please visit **globalBMG.com/hp/**.

1EO a/m² por ISO	526 T . M . I . I				
130 g/111- per 130	150 g/m² per ISO 536 Test Method				
290 g/m² per ISO 536 Test Method					
139 microns/5.5 mil per ISO 534 Test Method					
289 microns/11.4	289 microns/11.4 mil per ISO 534 Test Method				
Greater than 96%	Greater than 96% per TAPPI T-425 Test Method and ISO 2471 Test Method				
Matte	Matte				
15 to 35° C / 59 to	15 to 35° C / 59 to 95° F				
20 to 80% RH	20 to 80% RH				
75+ years, unlam	75+ years, unlaminated with Original HP 771 Vivid Photo Inks and Original HP 91 Photo Inks ¹				
,	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, and Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series ²				
Less than 5 minut	Less than 5 minutes (at 23° C, 50% RH)				
Yes					
2 years, unopene	2 years, unopened in original packaging				
15 to 35° C / 59 to	15 to 35° C / 59 to 95° F				
15 to 30% RH	15 to 30% RH				
Product of China	Product of China				
Product numbers	Roll sizes	UPC codes	Region		
C2T51A	914 mm x 20 m (36 in x 66 ft)	848412013627	North America, Europe		
C2T52A	1067 mm x 20 m (42 in x 66 ft)	848412013634	North America, Europe		
Warranty HP large format printing materials are free from defects in materials at statement please see globalBMG.com/hp/MediaWarranties .					
	139 microns/5.5 i 289 microns/11.4 Greater than 96% Matte 15 to 35° C / 59 to 20 to 80% RH 75+ years, unlam Moderately water Original HP 70 Ph Less than 5 minu Yes 2 years, unopene 15 to 35° C / 59 to 15 to 30% RH Product of China Product numbers C2T51A C2T52A HP large format p	139 microns/5.5 mil per ISO 534 Test Method 289 microns/11.4 mil per ISO 534 Test Method Greater than 96% per TAPPI T-425 Test Method and Matte 15 to 35° C / 59 to 95° F 20 to 80% RH 75+ years, unlaminated with Original HP 771 Vivid P Moderately water resistant with Original HP 771 Vivi Original HP 70 Photo Inks on the HP Designjet Z3200 Less than 5 minutes (at 23° C, 50% RH) Yes 2 years, unopened in original packaging 15 to 35° C / 59 to 95° F 15 to 30% RH Product of China Product numbers Roll sizes C2T51A 914 mm × 20 m (36 in × 66 ft) C2T52A 1067 mm × 20 m (42 in × 66 ft) HP large format printing materials are free from def	139 microns/5.5 mil per ISO 534 Test Method 289 microns/11.4 mil per ISO 534 Test Method Greater than 96% per TAPPI T-425 Test Method and ISO 2471 Test Method Matte 15 to 35° C / 59 to 95° F 20 to 80% RH 75+ years, unlaminated with Original HP 771 Vivid Photo Inks and Original Moderately water resistant with Original HP 771 Vivid Photo Inks, Original Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series Less than 5 minutes (at 23° C, 50% RH) Yes 2 years, unopened in original packaging 15 to 35° C / 59 to 95° F 15 to 30% RH Product numbers Roll sizes UPC codes C2T51A 914 mm x 20 m (36 in x 66 ft) 848412013627 C2T52A 1067 mm x 20 m (42 in x 66 ft) 848412013634 HP large format printing materials are free from defects in materials and		

¹ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhem Imaging Research, Inc. on a range of HP media. For more information, see **globalBMG.com/hp/t/printpermanence**.

For detailed information on the HP large format printing materials portfolio and to order, see ${\it globalBMG.com/hp}$

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: globalBMG.com/hp/t/printpermanence.