

HP Color LaserJet Enterprise M855 Printer series

Designed for businesses that want to boost productivity for every workgroup with fast, professional-quality colour printing and easy finishing options. Easily upgrade this enterprise printer as your organization's needs change.





Print at a speed that meets your needs

- Boost productivity for everyone in your organization with fast colour printing on different media sizes up to SRA3.
- Equip employees to fly through tasks with the large 10.9cm (4.3 inch) touchscreen.
- Show your company's true colours get vibrant, consistent and affordable colour printing for every
- HP's on paper calibration technology helps provide even, consistent colour—from page to page, and on every printer.
- Give employees the tools to organise documents faster. and more conveniently: Staple, stack, fold, and punch holes with the printer's optional finishing options¹.



- Expand your options. Easily upgrade firmware on your schedule and integrate new solutions or devices with
- Help build business efficiency. Centrally monitor and control printers with HP Web Jetadmin².
- Apply fleet-wide policies to help protect your HP devices with HP Imaging and Printing Security Center3.
- Confidently safeguard the sensitive data sent to the printer with the HP High-Performance Secure Hard Disk4.





- Give users simple, direct access to the printer through wireless direct printings.
- Get mobile printing at a touch with Near Field Communications (NFC): enable touch-to-print convenience from mobile devices
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software.
- Give users the power to print wirelessly from an iPad®, iPhone® or iPod touch® using AirPrint™8.











Document finishing accessories must be purchased separately. An input accessory with a stand must be installed for use before adding a finishing accessory.

HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

HP Imaging and Printing Security Center must be purchased separately.
 The HP High-Performance Secure Hard Disk is not available on the HP Color Laser Jet Enterprise M855dn model.

⁵ Wireless direct printing is standard in the HP LaserJet Enterprise M855x+ D7P73A model, and may be added as an option to the HP LaserJet Enterprise M855x+ A2W79A, HP LaserJet Enterprise M855xh A2W78A and HP LaserJet Enterprise M855dn A2W77A. Mobile device may require an app or driver. Wireless performance is dependent on physical environment and distance from the printer. For details, see hp.com/go/wirelessprinting.

⁶ Touch-to-print capability is standard in the HP LaserJet Enterprise M855x+ D7P73A model and may be added as an option to the HP LaserJet Enterprise M855x+ A2W79A, HP LaserJet Enterprise M855xh A2W78A and HP LaserJet Enterprise M855dn A2W77A. Mobile device must support near-field communications-enabled printing. For a list of supported devices, see hp.com/go/mobileprinting.

⁷ Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/qo/mobileprinting for more details.

Supports OS X® Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad® (all models), iPhone® (3GS or later), and iPhod touch® (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be connected to the same network as your OS X or iOS device. Wireless performance is dependent on physical environment and distance from the access point. OS X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc.

Product walkaround

HP Color LaserJet Enterprise M855x+ Printer shown:

- 1. Intuitive 10.9 cm colour touchscreen control panel
- 2. 500-page output bin
- 3. Front door provides convenient access to HP toner cartridges and drums
- 4. Built-in automatic two-sided printing
- 5. 500-sheet input tray supports media up to A3
- 6. 3,500-sheet high-capacity input tray supports A4 media
- 7. Easy-access USB port to print files directly
- 8. Hardware integration pocket (HIP) for solution integration
- 9. Right-side doors provide access for clearing jams
- 10. 100-sheet multipurpose tray handles media up to 220 g/m²
- 11. Access port for optional Kensington-style lock
- 12. 800 MHz processor, 1 GB standard memory
- 13. High-Speed USB 2.0 port (for connecting third-party devices)
- 14. Two internal host USB 2.0 type ports for third party solutions
- 15. HP Jetdirect Gigabit Ethernet print server
- 16. Hi-Speed USB 2.0 printing port
- 17. HP High-Performance Secure Hard Disk



Series at a glance



HP Color LaserJet Enterprise M855dn Printer

- Print speed of up to 46 ppm colour
- HP ImageREt 4800
- HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi
- HP ProRes 1200 (1200 x 1200 dpi)
- 800 MHz processor
- 1 Gigabit Ethernet 10/100/1000T network
- 2 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 1 hardware integration pocket
- 1 GB RAM
- SSD (min 8 GB volatile storage)
- 100-sheet multi-purpose tray
- 500-sheet input tray
- Optional: 1 x 500 sheet feeder and stand or 3 x 500 sheet feeder and stand or 1 x 3500 sheet feeder and stand



HP Color LaserJet Enterprise M855xh Printer

- As HP Color LaserJet Enterprise M855dn Printer with HP High-Performance Secure Hard Disk, minimum 320 GB, AES 256 hardware encryption or greater
- 3 x 500-sheet input tray with stand



HP Color LaserJet Enterprise M855x+ Printer

- As HP Color LaserJet Enterprise M855dn Printer with HP High-Performance Secure Hard Disk, minimum 320 GB, AES 256 hardware encryption or greater
- 3500-sheet high capacity input tray with stand



HP Color LaserJet Enterprise M855x+ NFC/Wireless Direct Printer

- As HP Color LaserJet Enterprise M855dn Printer with NFC/wireless direct accessory
- Wireless Direct Printing
- HP High-Performance Secure Hard Disk, minimum 320 GB, AES 256 hardware encryption or greater
- 3500-sheet high capacity input tray with stand

Recommended accessories



A2W80A HP Color LaserJet Stapler/Stacker

HP Color LaserJet Finishers improve workflow management by upgrading your printer to automatic stapling and sheet stacking. Monitor your printer less frequently with convenient automatic job stapling and sorting in the additional output bin.



A2W83A HP Color LaserJet Booklet Maker/Finisher

HP Color Laser Jet Finishers allow you to create complex documents with three bins, automatic offset, inline stapling and stacking and booklet making with saddle-stitching and v-folding.



C1N63A HP Color LaserJet 3x500-sheet Paper Feeder and Stand

Spend less time loading paper and more time printing. Meet the printing needs of a high-volume printing environment with the 3x500-sheet paper feeder and stand for HP Color LaserJet Enterprise flow M880 MFP & HP Color LaserJet Enterprise M855 Printer



C1N64A

HP Color LaserJet 1x3500-sheet Paper Feeder and Stand

Support the productivity of growing work groups with this high-performance, robust input feeder and stand. The additional 3,500-sheet paper capacity allows users to spend more time focusing on business and less time reloading paper.



J8029A HP Jetdirect 2800w NFC/Wireless Direct Accessory

This accessory enables wireless printing with touch-to-print convenience from NFC-capable devices or through a secure peer-to-peer connection from smartphones, tablets, and laptops. 1.2.3

Ordering information



Accessories

HP Color LaserJet Enterprise M855dn Printer (A2W77A)

HP Color LaserJet Enterprise M855dn Printer; Black, Cyan, Magenta and Yellow HP Color LaserJet Drums (yield ~30,000 pages); Black, Cyan, Magenta and Yellow HP Color LaserJet Toner Cartridges (yield ~29,000 pages black, ~31.500 pages colour); CD with software drivers and documentation; Documentation (Hardware Install Guide); power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); hardware integration pocket; Walk-up USB printing port; 100-sheet multipurpose tray 1; 500-sheet input tray 2; Automatic duplexer (built-in)



HP Color LaserJet Enterprise M855xh Printer (A2W78A)

HP Color LaserJet Enterprise M855xh Printer; Black, Cyan, Magenta and Yellow HP Color LaserJet Drums (yield ~30,000 pages); Black, Cyan, Magenta and Yellow HP Color LaserJet Toner Cartridges (yield ~29,000 pages black, ~31.500 pages colour); CD with software drivers and documentation; Documentation (Hardware Install Guide); power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Hardware integration pocket; Walk-up USB printing port; 100-sheet multipurpose tray 1; 500-sheet input tray 2; 3 x 500-sheet input tray with stand; Automatic duplexer (built-in); HP High-Performance Secure Hard Disk, minimum 320 GB, AES 256 hardware encryption or greater

Supplies



HP Color LaserJet Enterprise M855x+ Printer (A2W79A)

HP Color LaserJet Enterprise M855x+ Printer; Black, Cyan, Magenta and Yellow HP Color LaserJet Drums (yield ~30,000 pages); Black, Cyan, Magenta and Yellow HP Color LaserJet Toner Cartridges (yield ~29,000 pages black, ~31.500 pages colour); CD with software drivers and documentation; Documentation (Hardware Install Guide); power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Hardware integration pocket; Walk-up USB printing port; 100-sheet multipurpose tray 1; 500-sheet input tray 2; 3500-sheet high capacity input tray with stand; Automatic duplexer (built-in); HP High-Performance Secure Hard Disk, minimum 320 GB, AES 256 hardware encryption or greater



HP Color LaserJet Enterprise M855x+ NFC/Wireless Direct Printer (D7P73A)

HP Color LaserJet Enterprise M855x+ NFC/Wireless Direct Printer; Black, Cyan, Magenta and Yellow HP Color LaserJet Drums (yield ~30,000 pages); Black, Cyan, Magenta and Yellow HP Color LaserJet Toner Cartridges (yield ~29,000 pages black, ~31.500 pages colour); CD with software drivers and documentation; Documentation (Hardware Install Guide); power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Hardware integration pocket; Walk-up USB printing port; 100-sheet multipurpose tray 1; 500-sheet input tray 2; 3500-sheet high capacity input tray with stand; Automatic duplexer (built-in); HP High-Performance Secure Hard Disk, minimum 320 GB, AES 256 hardware encryption or greater; NFC/wireless direct accessory

Accessories, Supplies and Support

A2W80A	HP Color LaserJet Stapler/Stacker
A2W83A	HP Color Laser Jet Booklet Maker/Finisher
C1N63A	HP Color LaserJet 3x500-sheet Paper Feeder and Stand
C1N64A	HP Color LaserJet 1x3500-sheet Paper Feeder and Stand
C2H56A	HP LaserJet 1x500-sheet Paper Feeder and Stand
A2W82A	HP Color LaserJet Stapler/Stacker with 2/4 hole punch
CZ999A	HP Color Laser Jet Booklet Maker/Finisher with 2/4 hole punch
C8091A	HP Staple Cartridge Refill (5000 staples) for Stapler/Stacker accessories
CC383A	HP 2-pack 2000-staple Cartridge for booklet maker finisher
Connectiv	rity
J8029A	HP Jetdirect 2800w NFC/Wireless Direct Accessory
J8026A	HP Jetdirect 2700w USB Wireless Print Server

Juppucs	
C1N54A	HP LaserJet C1N54A 110V Maintenance Kit
	100,000 pages
C1N58A	HP LaserJet C1N58A 220V Maintenance Kit
	100,000 pages
D7H14A	HP LaserJet D7H14A Transfer and Roller Kit
	150,000 pages
CF310A	HP 826A Black Original LaserJet Toner Cartridge
	Average continuous Black Cartridge yield 29,000 standard
	pages. Declared yield value in accordance with ISO/IEC 19798.
CF311A	HP 826A Cyan Original LaserJet Toner Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 31,500 standard pages. Declared yield value in
	accordance with ISO/IEC 19798.
CF312A	HP 826A Yellow Original LaserJet Toner Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 31,500 standard pages. Declared yield value in
	accordance with ISO/IEC 19798.
CF313A	HP 826A Magenta Original LaserJet Toner Cartridge
	Average continuous composite Cyan/Yellow/Magenta
	Cartridge yield 31,500 standard pages. Declared yield value in
	accordance with ISO/IEC 19798.
CF358A	HP 828A Black LaserJet Image Drum
	30,000 pages
CF359A	HP 828A Cyan LaserJet Image Drum
	30,000 pages
CF364A	HP 828A Yellow LaserJet Image Drum
	30,000 pages
CF365A	HP 828A Magenta LaserJet Image Drum
	30,000 pages

Service & support

UOLW3E - HP 3 year Next Business Day Color LaserJet M855 Hardware Support

Support

VOLW6E - HP 3 year 4 hour 9x5 Color LaserJet M855 Hardware Support

UOLW4E - HP 4 year Next Business Day Color LaserJet M855 Hardware

UOLWSE - HP 5 year Next Business Day Color LaserJet M855 Hardware

WOLYAPE - HP 1 year Post-Warranty Next Business Day Color LaserJet M855 Hardware Support

UOLYGPE - HP 1 year Post-Warranty 4 hour 9x5 Color LaserJet M855 Hardware Support

UDLYSPE - HP 2 year Post-Warranty Next Business Day Color LaserJet M855 Hardware Support

For a complete list of supplies, accessories and services, please refer to http://www.hp.com For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Technical specifications

Print technology	Laser					
Print speed	A4 black: Up to 46 ppm, A4 colour: Up to 46 ppm, A4 duplex: Up to 43 ipm A3 black: Up to 22 ppm, A3 colour: Up to 22 ppm, A3 duplex: Up to 21 ipm First page out black (A4): As fast as 11 sec, First page out colour (A4): As fast as 11 sec, Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.					
Processor	800 MHz					
Memory	1 GB. Not expandable					
Hard disk	Only for D7P73A, A2W79A, A2W	78A: Standard, HP High-Performance Secure Hard Disk, r				
Print	Quality HP ImageRet 4800; HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi; HP ProRes 1200 (1200 x 1200 dpi); On Paper Calibration Technology, Pantone® Calib Resolution Black: Up to 1200 x 1200 dpi, Color: Up to 1200 x 1200 dpi Printer languages HP PCL 6, HP PCL 5, HP postscript level 3 emulation Typefaces/fonts 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Font Emulation available at hp.com/go/laserjetfonts Up to 175000 pages 4000 to 25000					
	volume					
	Print margins (mm)	Top: 2.1 mm. Left: 2.1 mm. Right: 2.1 mm. Bottom: 2	2.1 mm			
Media handling	Input: Tray 1	Capacity sheets: 100 (75 g/m²); envelopes: 10	Weight Tray 1: 60 to 220 g/m²	Size A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); Dpostcard (JIS), Envelopes: B5, C5, C6. DL		
	Tray 2 Tray 3	sheets: 500 (75 g/m²) A2W78A: Tray 3-5: sheets: 500 (75 g/m² media); A2W79A: Tray 3, sheets: 1500 (75 g/m² media); Tray 4, sheets: 2000 (75 g/m²); Tray 4, sheets: 2000 (75 g/m²); Tray 3, sheets: 1500 (75 g/m²); Tray 4, sheets: 2000 (75 g/m²);		A3, A4, A4-R, A5, B4 (JIS), B5 (JIS); RA4, SRA4 A2W78A: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS); RA4, SRA4; RA3; SRA3; A2W79A: A4; D7P73A: A4;		
	Output: Sheets: Up to 500 sheets (75 g/m²). Envelopes: Up to 60 envelopes. Transparencies: Up to 100 sheets Duplex printing: Automatic (standard)					
Media types		uaru; encies, glossy paper, glossy film, photo media, tough pap	par anyalanas			
Interface and connectivity		ost; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/10	1-1	kot (HID): 2 Intornal LISB Host		
	Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Lion, For the latest operating system support see: Citrix® and Windows Terminal Services (hp.com/go/dpd), HP ePrint Software Driver: hp.com/go/eprintsoftware, Linux (hplip.net), Novell® (novell.com/print), SAP device types hp.com/go/sap/drivers, SAP Print hp.com/go/sap/print), UNIX® hp.com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix_software. Latest printer driver information available at hp.com/support; go to hp.com/support Select your country/region; Select DRIVERS & SOFTWARE. Enter the product name/number. Under DOWNLOAD OPTIONS, select DRIVERS, SOFTWARE & FIRMWARE. If no access to Internet, see the install notes on the CD that came in the printer box.					
	Windows Server 2008 R2 (64-bi Terminal Services (hp.com/go/up hp.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS & CD that came in the printer box.	t), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), ol), HP ePrint Software Driver: hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix_so & SOFTWARE. Enter the product name/number. Under D(Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li , Linux (hplip.net), Novell® (novell.com/iprint), oftware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAF	SAP device types hp.com/go/sap/drivers, SAP Print toble at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the		
Network operating systems compatibility	Windows Server 2008 R2 (64-bi Terminal Services (hp.com/go/iµ hp.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS (CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (n), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), od), HP ePrint Software Driver: hp. com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix, S8, SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32-bit/64-bit); Windows Vista (32-bit/64-bit); Windows Vista (32-bit/64-bit); Windows Vista (32-bit/64-bit); Windows 2012 (64-bit); SP2 or higher; Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 11.i; IBIM® AIX 3.2.5 or higher; MPE-IX; Citrix® M.	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), fitware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAI -bit/64-bit); Windows Vista Ready; Windows X Windows Server 2008 (32-bit/64-bit); Window in Lion; RED HAT Linux 7.x or higher; Solaris®	on, For the latest operating system support see: Citrix® and Window: SAP device types hp.com/go/sap/drivers, SAP Print ible at hp.com/support; go to hp.com/support Select your		
Minimum system requirements	Windows Server 2008 R2 (64-bi Terminal Services (hp.com/gol/sp/print), UNIX® hp. country/region; Select DRIVERS & CD that came in the printer box. Windows 8 (32-bit/64-bit); Wind Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or h (64-bit); 200 MB available hard cystem requirements see micros (USB 1.1 or 2.0), or network con	t), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), d), HP ePrint Software Driver: hp.com/go/eprintsoftware com/go/unit, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware Driver Volume Driver Volume Volume Driver Volume Volume Volume Driver Volume	Mac OS X v10.6, v10.7. Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), flware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAF-bit/64-bit); Windows Vista Ready; Windows X; Windows Server 2008 (32-bit/64-bit); Windois Lion; RED HAT Linux 7.x or higher; Solaris® etaFrame Server; Windows Terminal Services. dows Server 2003 (SP1 or higher), Windows Se Dedicated universal serial bus (USB 1.1 or 2.0) m; 1 69 of available hard-disk space; CD-ROM requirements see apple.com	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print bible at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP		
Minimum system requirements Standard software	Windows Server 2008 R2 (64-bit) Terminal Services (hp.com/go/uphp.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS 2 CD that came in the printer box. Windows 8 (32-bit/64-bit); Wind Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows XP Professional Windows XP Windows Server 3091 or (64-bit); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver;	I), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), vid), HP ePrint Software Driver: hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix, So SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32-bit/64-bit); Windows Vista (32-bit/64-bit); Windows Server 2012 (64-bit); PSP2 or higher), Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 11.i; IBM® AIX 3.2.5 or higher; MPE-IX; Citrix® M. and Windows Vista) (sigher), Windows Vista) (s	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), fftware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAIbit/64-bit); Windows Vista Ready; Windows X Windows Server 2008 (32-bit/64-bit); Windows Lin Lion; RED HAT Linux 7.x or higher; Solaris® etaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Se Dedicated universal serial bus (USB 1.1 or 2.0) n; 1 GB of available hard-disk space; CD-ROM requirements see apple.com	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print blbe at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2012, or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus		
Minimum system requirements Standard software Control panel	Windows Server 2008 R2 (64-bit Terminal Services (hp.com/go/uph.com/go/sp/print), UNIX® hp. country/region; Select DRIVERS 5. CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows R9 (SP3 or higher) Prof (64-bit); Windows Server 2003 (hovell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or 164-bit); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchsc	t), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), od), HP ePrint Software Driver: hp. com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix, Se, SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 essional; Windows 2000; Windows Server 2012 (64-bit); SP2 or higher); Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 111; IBIN® AIX 3.2.5 or higher; MPE-IX; Citrix® M. and Windows Vista) windows XP (SP2 or higher), Windows Vista, Windows XP (SP2 or higher), Windows Vista, Windows XP (SP2 or higher), Windows (154 bit), windows Vista, Windows XP (SP2 or higher), Windows (154 bit), windows (15	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), Vifware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAI -bit/64-bit); Windows Vista Ready; Windows X windows Server 2008 (32-bit/64-bit); Windows Lin Lion; RED HAT Linux 7.x or higher; Solaris® etaFrame Server; Windows Terminal Services. dows Server 2003 (SP1 or higher), Windows Se Dedicated universal serial bus (USB 1.1 or 2.0) n; 1 GB of available hard-disk space; CD-ROM requirements see apple.com	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print ble at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2008 R2 (64 bit); Windows Server 2012; or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus of the memon); Easy Access USB; Hardware Integration Pocket		
Minimum system requirements Standard software	Windows Server 2008 R2 (64-bit Terminal Services (hp.com/go/sp/print), UNIX® hp. country/region; Select DRIVERS (CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or the (64-bit); COM MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchsc Requirements: Input Voltage: 22	t), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), vld), HP ePrint Software Driver: hp.com/go/eprintsoftware com/go/lwii, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware cows & SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 essional; Windows 2000; Windows Server 2012 (64-bit); SP2 or higher); Mac 05 X v10.6, v10.7 Lion, v10.8 Mounta (20, 11.x, 11.1; IBM® AIX 3.2.5 or higher; MPE-iX; Citrix® Mi. and Windows Vista) iigher), Windows Vista, Windows XP (SP2 or higher), Windisk space; CD-ROM or DVD drive, or Internet connection; offt.com. Mac 05 X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system: mac Software Link to Web (Mac Installer); Windows Insta reen; rotating (adjustable angle) display; illuminated Capo (10 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A. Consump	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/lprint), Vifware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAIDWNLOAD OPTIONS, select DRIVERS, SOFTWAIDWNLOAD OPTIONS, select DRIVERS, SOFTWAIDWNLOAD OPTIONS, Select DRIVERS, SOFTWAIDWNLOAD OPTIONS, SELECT SOFT WINDOWS SELECT SOFT OPTION OPTIO	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print blbe at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2012, or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h)	Windows Server 2008 R2 (64-bi Terminal Services (hp.com/gol/sp/print), UNIX® hp. country/region; Select DRIVERS (CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (7 Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or the (64-bit); CO MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchsc Requirements: Input Voltage: 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704 : A2W78A: 856 x 790 x 1352 mir	t), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), vld), HP ePrint Software Driver: hp.com/go/eprintsoftware com/go/lwi, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/eprintsoftware com/go/unix of higher); Windows Vista (32-essional; Windows 2000; Windows Server 2012 (64-bit); SP2 or higher); Mac 05 X v10.6, v10.7 Lion, v10.8 Mounta (20, 11.x, 11.i; IBM® AIX 3.2.5 or higher; MPE-iX; Citrix® Mi. and Windows Vista) iigher), Windows Vista) iigher), Windows Vista, Windows XP (SP2 or higher); Windows Vista) iigher), Windows Vista, Windows XP (SP2 or higher), Windisk space; CD-ROM or DVD drive, or Internet connection; offt.com. Mac 05 X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system: Mac Software Link to Web (Mac Installer); Windows Insta reen; rotating (adjustable angle) display; illuminated Cape to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A. Consum; Week. Power requirements are based on the country/reg	Mac OS X v10.6, v10.7, Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/lprint), Vintware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAIDMNLOAD OPTIONS, Windows Severer 2008 (32-bit/64-bit); Windows Severer 2008 (32-bit/64-bit); Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Server 2003 (SP1 or higher), Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Server 2008 (JP2), Windows Mindows Server 2008 (JP2), Windows Mindows Server 2008 (JP2), Windows Mindows Server 2008 (JP2), Windows Mindows Mi	on, For the latest operating system support see: Citrix® and Windows SAP device types by.com/go/sap/drivers, SAP Print bible at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP (SPARC® or DVD drive, or Internet connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus on the menu); Easy Access USB; Hardware Integration Pocket 7.0 watts (sleep), 1 watt (auto-off), 0.4 watts (off). Typical Electricity perating voltages. This will damage the printer and void the product (635 x 1063 mm; ; Packaged: A2W77A: 856 x 790 x 899 mm;		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight	Windows Server 2008 R2 (64-bi Terminal Services (hp.com/gol/sp/print), UNIX® hp. country/region; Select DRIVERS of CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows XP (SP3 or higher) Prof (64-bit); Windows SYP (SP3 or higher) Prof (64-bit); Windows Server 2003 (10-bit); You May (10-bit); You Mindows 7 (SP1 or higher); HP-UX 10. Home, Windows 7 (SP1 or higher); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchsc Requirements: Input Voltage: 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704: A2W78A: 856 x 790 x 1352 mr	t), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), d), HP ePrint Software Driver: hp.com/go/eprintsoftware com/go/en; UNIW 3 letDirect hp.com/go/eprintsoftware com/go/en; UNIW 3 let be product name/number. Under D(ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 essional; Windows 2000; Windows Server 2012 (64-bit); SP2 or higher); Mac 05 X v10.6, v10.7 Lion, v10.8 Mounta in Links pace; CD-ROM or DVD drive, or Internet connection; offt.com. Mac 05 X v10.6, v10.7 Lion, v10.8 Mountain Linection; Operating system compatible hardware system: Mac Software Link to Web (Mac Installer); Windows Insta reen; rotating (adjustable angle) display; illuminated Cap 0 to 240 VAC (+f- 10%), 50 Hz (+f- 2 Hz), 5.5 A. Consumy Week. Power requirements are based on the country/reg x635 x 580 mm; A2W79A: 856 x 790 x 1352 mm; D7P73A: 856 x 798 Rg, A2W79A: 124.08 kg, D7P73B; Rg, A2W79A; 124.08	Mac OS X v10.6, v10.7, Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/lprint), Vintware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAIDMNLOAD OPTIONS, Windows Severer 2008 (32-bit/64-bit); Windows Severer 2008 (32-bit/64-bit); Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Server 2003 (SP1 or higher), Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Server 2003 (SP1 or higher), Windows SetaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Server 2008 (JP2), Windows Mindows Server 2008 (JP2), Windows Mindows Server 2008 (JP2), Windows Mindows Server 2008 (JP2), Windows Mindows Mi	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print ble at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2008 R2 (64 bit); Windows Server 2012; or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus of the memuly; Easy Access USB; Hardware Integration Pocket 7.0 watts (sleep), 1 watt (auto-off), 0.4 watts (off). Typical Electricity perating voltages. This will damage the printer and void the product		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Windows Server 2008 R2 (64-bit) Terminal Services (hp.com/go/uphp.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS 2 CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows 8 (32-bit/64-bit); Windows P(SP3 or higher) Prof (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or h (64-bit); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchso Requirements: Input Voltage: 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704: A2W78A: 856 x 790 x 1352 m Out of package: A2W77A: 36.2! HP Web Jetadmin; HP Utility (Ma	d), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), od), HP ePrint Software Driver: hp. com/go/perintsoftware com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix, Sc 8. SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32-essional; Windows 2000; Windows Server 2012 (64-bit); Sep2 or higher), Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 11.1; IBN® AIX 3.2.5 or higher; MPE-IX; Citrix® M; and Windows Vista). Windows Vista, Windows XP (SP2 or higher), Windisk space; CD-ROM or DVD drive, or Internet connection; Soft.com. Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system; Mac Software Link to Web (Mac Installer); Windows Instaireen; rotating (adjustable angle) display; illuminated Cap 010 240 VAC (+/-109k), 50 Hz (+/-2 Hz), 5.5 A. Consum; Week. Power requirements are based on the country/reg x635 x 80 mm; A2W78A: 704 x 635 x 1063 mm; A2W m; A2W79A: 856 x 790 x 1352 mm; D7P73A: 856 x 798 kg; A2W79A: 124.08 kg; D7P73 b).	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), offtware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAI -bit/64-bit); Windows Vista Ready; Windows X ewer 2008 (32-bit/64-bit); Windows Lin Lion; RED HAT Linux 7.x or higher; Solaris® etaFrame Server; Windows Terminal Services. dows Server 2003 (SP1 or higher), Windows Sedicated universal serial bus (USB 1.1 or 2.0) n; 1 GB of available hard-disk space; CD-ROM requirements see apple.com liler active Home button (for quick return to the Hotion: 1100 watts (printing), 60 watts (ready), ion where the printer is sold. Do not convert of the converse of t	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print ble at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher; (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2012, or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus of the menu); Easy Access USB; Hardware Integration Pocket 7.0 watts (sleep), 1 watt (auto-off), 0.4 watts (off). Typical Electricity poerating voltages. This will damage the printer and void the product 6:635 x 1063 mm;; Packaged: A2W77A: 856 x 790 x 899 mm; kg; A2W78A: 141.9 kg; A2W79A: 142.9 kg; D7P73A: 142.9 kg;		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Windows Server 2008 R2 (64-bit Terminal Services (hp.com/go/kph.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS 5. CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows 8 (32-bit/64-bit); Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows XP Professional Windows 10, 20, or network country 10, 20, or network common HP PCL 6 Discrete Printer Criver; 10.9 cm colour LCD with touchsc. Requirements: Input Voltage: 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704: A2W78A: 855 x 790 x 1352 mr. 42W78A: 86.21 HP Web Jetadmin; HP Utility (Ma Identity Management: Kerberos. Certificate, Pre-Shared Key, and 15 torage Encryption, Secure Eraswith HP Imaging & Printing Secu	I), Windows Server 2003 (SP2 or higher) (32-bit/64-bit), vld), HP ePrint Software Driver: hp. com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp. com/go/eprintsoftware 28. SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 cessional; Windows 2000; Windows Server 2012 (64-bit); SP2 or higher), Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 111; IBIN® AIX 3.2.5 or higher; MPE-IX; Citrix® M. and Windows Vista). Windows Vista, Windows XP (SP2 or higher), Windisk space; (D-ROM or DVD drive, or Internet connection; Soft.com. Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system: Mac Software Link to Web (Mac Installer); Windows Instateren; rotating (adjustable angle) display; illuminated Cap. 0 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A. Consum; Week. Power requirements are based on the country/reg x635 x 780 mm; A2W79A: 256 x 790 x 1352 mm; D7P73A: 856 x 79 s A2W79A: 124.08 kg; D7P73; c). authentication, LDAP authentication, 1000 user PIN code xerberos authentication, Supports WJA-10 IPsec configure, sSL/TLS, Encrypted Credentials; Device: Security lock sitly Center	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), Vifware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAIDWNLOAD OPTIONS, Windows Server 2008 (32-bit/64-bit); Windows Server 2008 (32-bit/64-bit); Windows Server 2003 (SP1 or higher; Solaris® etaFrame Server; Windows Terminal Services. Jowns Server 2003 (SP1 or higher), Windows Services. Jowns Server 2003 (SP1 or higher), Windows Server 2003 (SP1	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print bible at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher (SPARC® systems only); SUSE Linux 8.x or higher (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2008 R2 (64 bit); Windows Server 2012 c, or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Seri		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment	Windows Server 2008 R2 (64-bit) Terminal Services (hp.com/go/uphp.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS 2 CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows 8 (32-bit/64-bit); Windows YE (SP3 or higher) Prof (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or h (64-bit); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchso Requirements: Input Voltage: 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704: A2W78A: 856 x 790 x 1352 m Out of package: A2W77A: 36.2! HP Web Jetadmin; HP Utility (Ma Identity Management: Kerberos. Certificate, Pre-Shared Key, and Storage Encryption, Secure Eras with HP Imaging & Printing Secu	to, Windows Server 2003 (SP2 or higher) (32-bit/64-bit), od), HP ePrint Software Driver: hp. com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp.com/go/jetdirectunix, Sc 3. SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 essional; Windows 2000; Windows Server 2012 (64-bit); Sep2 or higher), Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 11.i; IBN® AIX 3.2.5 or higher; MPE-IX; Citrix® M; and Windows Vista). Windows Vista, Windows XP (SP2 or higher), Windidows Vista, Windows XP (SP2 or higher), Windidows Vista, Windows XP (SP2 or higher), Windidows Vista, Windows XP (SP2 or higher), Windows Vista, Windows OS X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system; Mac Software Link to Web (Mac Installer); Windows Instateren; rotating (adjustable angle) display; illuminated Cap 010 240 VAC (+/-109A), 50 Hz (+/-2 Hz), 5.5 A. Consum; Week. Power requirements are based on the country/reg X635 x 580 mm; A2W78A: 704 x 635 x 1063 mm; A2W79A: 856 x 790 x 1352 mm; D7P73A: 856 x 798 B kg; A2W79A: 122.47 kg; A2W79A: 124.08 kg; D7P7: c) authentication, LDAP authentication, 1000 user section; lock srity Center (Yc. Recommended operating temperature: 15 to 30°C . 1996 RH	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), Vifware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAIDWNLOAD OPTIONS, Windows Server 2008 (32-bit/64-bit); Windows Server 2008 (32-bit/64-bit); Windows Server 2003 (SP1 or higher; Solaris® etaFrame Server; Windows Terminal Services. Jowns Server 2003 (SP1 or higher), Windows Services. Jowns Server 2003 (SP1 or higher), Windows Server 2003 (SP1	on, For the latest operating system support see: Citrix® and Windows SAP device types by.com/go/sap/drivers, SAP Print bible at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows Server 2008 R2 (64-bit); Windows 2003, Windows Server 2012, or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus on the menu); Easy Access USB; Hardware Integration Pocket 7.0 watts (sleep), 1 watt (auto-off), 0.4 watts (off). Typical Electricity perating voltages. This will damage the printer and void the product 6.635 x 1063 mm;; Packaged: A2W77A: 856 x 790 x 899 mm; kg; A2W78A: 141.9 kg; A2W79A: 142.9 kg; D7P73A: 142.9 kg; Lication solutions (e.g., badge readers); Network: IPSec/firewall with AP EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control List; Data:		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Windows Server 2008 R2 (64-bi) Terminal Services (hp.com/go/uph.com/go/sap/print), UNIX® hp. country/region; Select DRIVERS 2. CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows 8 (32-bit/64-bit); Windows XP (SP3 or higher) Prof (64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or h (64-bit); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchso Requirements: Input Voltage; 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704 A2W78A: 856 x 790 x 1352 in Unit of package: A2W77A: 86.2 HP Web Jetadmin; HP Utility (Ma Identity Management: Kerberos Certificate, Pre-Shared Key, and I Storage Encryption, Secure Eras with HP Imaging & Printing Secu Operating temperature: 15 to 3 35°C. Storage humidity: 10 to 94 Acoustic Power Emissions: 7.1 B	 Mindows Server 2003 (SP2 or higher) (32-bit/64-bit), and), HP ePrint Software Driver: hp. com/go/eprintsoftware com/go/enits, UNIX® JetDirect hp. com/go/eprintsoftware com/go/unix, UNIX® JetDirect hp. com/go/pitdirectunix, Sp. 3 SOFTWARE. Enter the product name/number. Under DC ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 essional; Windows 2000; Windows Server 2012 (64-bit); Sep2 or higher) Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 11.i; IBIN® AIX 3.2.5 or higher; MPE-IX; Citrix® M. and Windows Vista) Mindows Vista, Windows XP (SP2 or higher), Windows Vista, and Windows Vista) Migher), Windows Vista, Windows XP (SP2 or higher), Windows Vista ingher), Windows Vista Mindows Vista, Windows XP (SP2 or higher), Windows Instaleron, Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system: Mac Software Link to Web (Mac Installer); Windows Instaleren; rotating (adjustable angle) display; illuminated Cap 0 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A. Consump Week. Power requirements are based on the country/reg x635 x580 mm; A2W78A: 704 x 635 x 1063 mm; A2W 78A: 124.08 kg; D7P73 c) Mac XW79A: 856 x 790 x 1352 mm; D7P73A: 856 x 79 s) as ba; A2W79A: 124.08 kg; D7P73 c) Coutherication, LDAP authentication, 1000 user PIN code Kerberos authentication, Supports WJA-10 IPsec configure, SSI/TLS, Encrypted Credentials; Device: Security lock s rity Center F. Recommended operating temperature: 15 to 30°C. 100 RH (A); Acoustic Pressure Emissions: 55 dB(A) 	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), Uriware, Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAI -bit/64-bit); Windows Vista Ready; Windows Xever 2008 (32-bit/64-bit); Windows Linux RED HAT Linux 7.x or higher; Solaris® etaFrame Server; Windows Terminal Services. dows Server 2003 (SP1 or higher), Windows Sebedicated universal serial bus (USB 1.1 or 2.0) n; 1 GB of available hard-disk space; CD-ROM requirements see apple.com liler actitive Home button (for quick return to the Hotion: 1100 watts (printing), 60 watts (ready), ion where the printer is sold. Do not convert of visual services with the printer is sold. Do not convert of visual services with the visual services with the visual services. Services with the visual services. The visual services with the visual servic	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print ble at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP erver 2008; Windows Server 2008 R2 (64 bit); Windows Server 2012; or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DVD drive, or Internet, DVD drive, DVD dr		
Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment	Windows Server 2008 R2 (64-bit Terminal Services (hp.com/go/lyhp.com/go/sap/print), UNIX® hp.country/region; Select DRIVERS 2 CD that came in the printer box. Windows 8 (32-bit/64-bit); Windows 8 (32-bit/64-bit); Windows 8 (36-bit/64-bit); Windows 8 (97-bit/64-bit); Windows Server 2003 (Novell® 5.1 or higher; HP-UX 10. Home, Windows XP Professional Windows 8, Windows 7 (SP1 or 164-bit); 200 MB available hard c system requirements see micros (USB 1.1 or 2.0), or network con HP PCL 6 Discrete Printer Driver; 10.9 cm colour LCD with touchsc Requirements: Input Voltage; 22 Consumption (TEC): 5.345 kWh/warranty. Out of package: A2W77A: 704 A2W78A: 856 x 790 x 1352 m Out of package; A2W77A: 765.21 HP Web Jetadmin; HP Utility (Ma Identity Management: Kerberos. Certificate, Pre-Shared Key, and Storage Encryption, Secure Eraswith HP Imaging & Printing Secu Operating temperature: 15 to 335°C. Storage humidity: 10 to 90 Acoustic Power Emissions: 7.1 B CISPR 22:2008/EN 55022:2010 required by individual countries.	 Mindows Server 2003 (SP2 or higher) (32-bit/64-bit), and), HP ePrint Software Driver: hp. com/go/eprintsoftware com/go/units, UNIX® JetDirect hp. com/go/pitelirectunix_sc. Sc SOFTWARE. Enter the product name/number. Under DG ows 7 (SP1 or higher) (32-bit/64-bit); Windows Vista (32 essional; Windows 2000; Windows Server 2012 (64-bit); SP2 or higher; Mac OS X v10.6, v10.7 Lion, v10.8 Mounta 20, 11.x, 11.i; IBIN® AIX 3.2.5 or higher; MPE-IX; Citrix® M. and Windows Vista) Mindows Vista, Windows XP (SP2 or higher), Windows Vista ingiher), Windows Vista, Windows XP (SP2 or higher), Windows Vista, and Windows Vista, and Windows Vista ingiher), Windows Vista ingiher), Windows Vista ingiher), Windows Vista ingiher, Windows Vista ingiher, Vindow Installer); Windows OS X v10.6, v10.7 Lion, v10.8 Mountain Lionection; Operating system compatible hardware system: Mac Software Link to Web (Mac Installer); Windows Installeren; rotating (adjustable angle) display; illuminated Cap 0 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 5.5 A. Consump Week. Power requirements are based on the country/reg x635 x 580 mm; A2W79A: 704 x 635 x 1063 mm; A2W m; A2W79A: 124.08 kg; D7P7: c) Beig; A2W79A: 152.47 kg; A2W79A: 124.08 kg; D7P7: c) Buthentication, LDAP authentication, 1000 user PIN code Kerberos authentication, Supports WJA-10 IPsec configure, SSL/TLS, Encrypted Credentials; Device: Security lock srity Center Recommended operating temperature: 15 to 30°C. 100 RH (A); Acoustic Pressure Emissions: 55 dB(A) (Class A); EN 61000-3-2; 2006+A1:2009 +A2:2009; EN 6 Regulatory standards: IEC 60950-1:2005 +A1; EN60950 at 4000 Enter Proper, EC 62479:2010; EN 62479:20	Mac OS X v10.6, v10.7 Lion, v10.8 Mountain Li, Linux (hplip.net), Novell® (novell.com/iprint), fftware. Latest printer driver information availa DWNLOAD OPTIONS, select DRIVERS, SOFTWAI -bit/64-bit); Windows Vista Ready; Windows X windows Server 2008 (32-bit/64-bit); Windows Lichor, RED HAT Linux 7.x or higher; Solaris® etaFrame Server; Windows Terminal Services. Jows Server 2003 (SP1 or higher), Windows Scoedicated universal serial bus (USB 1.1 or 2.0) n; 1 GB of available hard-disk space; CD-ROM requirements see apple.com ller active Home button (for quick return to the Hation: 1100 watts (printing), 60 watts (ready), ion where the printer is sold. Do not convert of the convertion of t	on, For the latest operating system support see: Citrix® and Windows SAP device types hp.com/go/sap/drivers, SAP Print ble at hp.com/support; go to hp.com/support Select your RE & FIRMWARE. If no access to Internet, see the install notes on the P (SP3 or higher) (64-bit); Windows XP (SP3 or higher) Home; ws Server 2008 R2 (64-bit); Windows Server 2003 (SP2 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP (SP3 or higher) 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; (For Microsoft IPv6 compatibility use Windows 2003, Windows XP (SP3 or network connection; Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus of DVD drive, or Internet Connection; Dedicated Universal Serial Bus or DvD drive, or Internet Connection; Dedicated Universal Serial Bus or DvD drive, or Internet Connection; Dedicated Universal Serial Bus or DvD drive, or Internet Connection; Dedicated Universal Serial Bus or DvD drive, or Internet Connection; DvD drive, or Internet, DvD drive, or Internet, DvD drive, DvD drive, DvD drive, DvD drive, DvD		



