






The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



- HP Everyday Adhesive Matte Polypropylene can be easily removed. Residual adhesive can be easily wiped clean. Some warranty limitations apply, see the Limited Warranty statement at globalBMG.com/hp/MediaWarranties.
- With Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series. Display permanence rating for interior displays/ away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/ printpermanence.
- Requires 2-inch spindle for compatibility with the HP Designjet L25500 and L26500 Printer series.

High-quality prints for your day-to-day production

Produce eye-catching displays

See outstanding image quality. Work with the wide color gamut and smooth transitions delivered by this matte polypropylene material and produce quality prints from line drawings to photo-quality POP displays.

Gain efficiency

Help keep your production process moving smoothly. This easy-to-use film features a permanent self adhesive for secure, reliable mounting. Instant-dry prints can be easily removed ¹

Make the versatility of this material work for you

ICC profiles help you get the right color, right away. Take advantage of compatibility with HP dye and pigment inks. Offer over 50 years unlaminated indoor display permanence,² on this versatile, easy-to-use printing material.

Target customers	Applications	Benefits	
Print service providers	POP and retail displays	Outstanding image quality for day-to-day production	
Retail store in-house printing	Trade show and event displays	Instant dry time	
Event designers	Temporary exhibitions	A permanent self-adhesive for secure, reliable mounting	
Advertising agencies	Architecture competitions	Compatible with both HP dye- and pigment- based inks	
Geographic Information Systems (GIS) Government (printing self-adhesive maps)		50+ years unlaminated indoor display permanence on HP Designjet Z-series printers ²	
		Easy to use and remove, with a limited HP warranty ¹	
		Broad HP Designjet printer compatibility ³	

Technical specifications



HP Everyday Adhesive Matte Polypropylene, 2 Pack

For the latest ICC/media profiles and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit globalBMG.com/hp/.

Weight (without liner)	120 g/m² per IS0	120 g/m² per ISO 536 Test Method						
Weight (with liner)	168 g/m² per ISI	168 g/m² per ISO 536 Test Method						
Thickness (without liner)	180 microns/7.1	180 microns/7.1 mil per ISO 534 Test Method						
Thickness (with liner)	215 microns/8.5 mil per ISO 534 Test Method							
Opacity (with liner)	Greater than 96% per TAPPI T-425 and ISO 2471 Test Methods							
Brightness (with liner)	101% per ISO 2470 Test Method							
Whiteness (without liner)	Greater than 120 per ISO 11476 Test Method							
Whiteness (with liner)	150 per ISO 11475 Test Method							
Finish	Matte							
Operating temperature	15 to 35° C / 59 to 95° F							
Operating humidity	20 to 80% RH	20 to 80% RH						
Display permanence	50+ years unlaminated with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70							
(Indoor home or office)	Photo Inks on the HP Designjet Z3200 Photo Printer series ⁴							
Water resistance	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series; lamination recommended with Original HP dye inks ⁵							
Dry time	Less than 2 minutes (at 23° C, 50% RH)							
Lamination	Yes							
Shelf life	2 years, unopened in original packaging							
Storage temperature	15 to 35° C / 59 to 95° F							
Storage humidity	15 to 30% RH							
Country of origin	Product of China							
Ordering information	Product numbers	s Quantity	Roll sizes	UPC Codes	Region			
	COF18A ⁶	2 Pack	610 mm x 22,9 m (24 in x75 ft)	848412012934	Americas, Europe			
	COF19A ⁶	2 Pack	914 mm x 22,9 m (36 in x75 ft)	848412012941	Americas, Europe			
	COF20A ⁶	2 Pack	1067 mm x 22,9 m (42 in x 75 ft)	848412012958	Americas, Europe			
	COF22A ⁶	2 Pack	1524 mm x 22,9 m (60 in x 75 ft)	848412012965	Americas, Europe			
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see globalBMG.com/hp/MediaWarranties .							

- ⁴ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see **globalBMG.com/hp/t/printpermanence**.
- Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see **globalBMG.** com/hp/t/printpermanence.
- ⁶ Requires 2-inch spindle for compatibility with the HP Latex 260.

For detailed information on the HP large format printing materials portfolio and to order, see ${\bf globalBMG.com/hp}$

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

