



APC Notebook Surge Protector for AC, phone and network lines, 2 pin connection, 100-240V, EMEA
Part Number: PNOTEPROC8-EC



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Ratings and Reviews](#)

Output

Number of Outlets	1
Receptacle Style	IEC 320-C8

Input

Nominal Input Voltage	230V
Input Power	575 Watts
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	IEC 320 C8
Maximum Line Current per phase	4A

Surge Protection and Filtering

Surge energy rating	180 Joules
Peak Current Normal Mode	6.50 kAmps
NM Surge Response Time (ns)	1 ns
Data Line Protection	RJ-11 Modem/Fax protection (two wire single line), RJ45 10/100 Base-T Ethernet protection
Let Through Voltage Rating	< 330

Physical

Net Weight	0.10 KG
Maximum Height	27.00 mm
Maximum Width	32.00 mm
Maximum Depth	98.00 mm
Shipping Weight	0.20 KG
Shipping Height	66.00 mm
Shipping Width	158.00 mm

Shipping Depth	192.00 mm
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	16.5 X 11.5 X 8.3 inches
Master Carton Weight	6.00 lbs.
Color	Silver
Units per Pallet	480.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-9000 meters

Conformance

Regulatory Approvals	A-tick, CE, CSA, FCC Part 68, GS Mark, NOM, TelePermit, UL Listed, VDE
Standard Warranty	5 years (all other countries), Lifetime (European Union countries only)
UL 1449 TVSS Rating	700V

Sustainable Offer Status

RoHS	Compliant
------	-----------