



APC Performance SurgeArrest 8 (1 PLC Compatible) outlets with Phone and Coax Protection 230V Germany

Part Number: PL8VT3-DE



[Technical Specifications](#) [Product Overview](#) [Documentation](#) [Ratings and Reviews](#)

Output

Number of Outlets	8
Receptacle Style	CEE 7 Schuko

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Input Connections	Schuko CEE 7/7P



Cord Length	2.44 meters
Maximum Input Current	10A
Input Breaker Capacity	10 A

Surge Protection and Filtering

Surge energy rating	2500 Joules
EMI/RFI Noise rejection (100 kHz to 10 MHz)	70 dB
Peak Current Normal Mode	37.50 kAmps
Peak Current Common Mode	37.50 kAmps
NM Surge Response Time (ns)	1 ns
Data Line Protection	RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines), Cable modem / Video protection

Physical

Net Weight	1.23 KG
Maximum Height	372.00 mm
Maximum Width	122.00 mm
Maximum Depth	42.00 mm
Shipping Weight	1.32 KG
Shipping Height	381.00 mm
Shipping Width	216.00 mm
Shipping Depth	51.00 mm
Master Carton Units	12.00
Master Carton Dimensions (Length x Width x Height)	689 x 228.6 x 387.4 mm
SCC Codes	1073130428139 6
Color	Black

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-40 - 85 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CE
Standard Warranty	Lifetime (European Union countries only)

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs