



**APC Smart-UPS 1500VA LCD 230V**  
**Part Number: SMT1500I**



[Technical Specifications](#)   [Product Overview](#)   [Documentation](#)   [Software & Firmware](#)   [Options](#)   [Ratings and Reviews](#)

### Output

Output Power Capacity	1000 Watts / 1500 VA
Max Configurable Power	1000 Watts / 1500 VA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Other Output Voltages	220, 240
Topology	Line Interactive
Waveform Type	Sine wave
Output Connections	(8) IEC 320 C13  (2) IEC Jumpers



### Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.83 meters
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for	151 - 302V

mains operation

Other Input Voltages 220, 240

### Batteries & Runtime


Battery Type Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time 3 hour(s)

Replacement Battery [RBC7](#)

RBC™ Quantity 1

Runtime Graph



*Hover over the line on the graph above to view the runtime at any desired load*


Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.

[View Enlarged Graph](#)

[View Runtime Chart](#)

### Energy Use/Efficiency

Load	Efficiency
25%	95.4%
50%	97.4%
75%	98.0%
100%	98.2%



*Hover over the line on the graph above to view the efficiency at any desired load*

Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.

[View Enlarged Graph](#)

## Communications & Management

Interface Port(s)	SmartSlot, USB
Available SmartSlot™ Interface Quantity	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	--

## Surge Protection and Filtering

Surge energy rating	459 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	219.00 mm
Maximum Width	171.00 mm
Maximum Depth	439.00 mm
Net Weight	24.09 KG
Shipping Weight	27.23 KG
Shipping Height	376.00 mm
Shipping Width	328.00 mm
Shipping Depth	595.00 mm
Color	Black
Units per Pallet	12.00

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Audible noise at 1 meter from surface of unit 45.00 dBA

Online Thermal Dissipation 135.00 BTU/hr

### Conformance

Regulatory Approvals C-tick, CE, EN 50091-1, EN 50091-2, VDE

Standard Warranty 3 years repair or replace (excluding battery) and 2 year for battery

### Sustainable Offer Status

RoHS Compliant

REACH REACH: Contains No SVHCs

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.