

HP Color LaserJet Enterprise flow M880 Multifunction Printer series

Designed for businesses wanting to accelerate and streamline workflows with an MFP that easily connects users across the office. Keep projects moving with easy send-to and finishing options plus mobile printing and touch-to-print capabilities^{1,2}.





Give workgroups the speed they need.

- Let departments scan without worry: HP EveryPage detects potential errors or missed pages on the spot.
- Manage content in a way you never thought possible with HP Flow CM Enterprise³.
- Forget email let employees scan and send documents to Microsoft® SharePoint® in one step.
- Make it easy to be efficient with an intuitive touchscreen and large pull-out keyboard.



- Save on both sides capture documents faster with two-sided, single-pass scanning.
- Create easily searchable scanned files, using built-in optical character recognition software.
- Save IT time and make printing easy for the entire company by using a single driver for all HP devices⁴.
- Let employees complete big jobs faster, choosing from a range of finishing options⁵.

Be much more efficient with mobile printing.

- Give users simple, direct access through wireless direct printing and touch-to-print technology⁶.
- Mobile printing at a touch enable touch-to-print convenience from mobile devices².
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software¹.
- Give users the power to print wirelessly from an iPad®, iPhone®, or iPod touch®.

Invest once, expand easily and manage efficiently.

- Expand your options: easily upgrade firmware on your schedule, and easily integrate solutions or devices at
 will
- Help build business efficiency. Centrally monitor and control printers with HP Web Jetadmin⁸.
- Apply fleet-wide policies to help protect all your HP devices with the HP Imaging and Printing Center⁹.
- Confidently safeguard the sensitive data sent to your MFP with the HP High-Performance Secure Hard Disk.











¹ Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for covariage and availability in your area. See hp.com/ac/mobileprinting for more details.

² Touch-to-print capability is standard in the HP Color LaserJet Enterprise flow MFP M880z + D7P71A model, and may be added as an option to the HP Color LaserJet Enterprise flow MFP M880z + A2W76A and M880z A2W75A. Mobile device must support near-field communications-enabled printing. For a list of supported devices, see hp.com/go/mobileprinting.

support near-neid communications-enabled printing. For a list of supported devices, see np.com/go/mobileprinting.

3 HP Flow CM is not available in all regions. Network connection is required to upload and download files. Additional software and licenses may be required.

⁴ The HP Universal Print Driver is free and available for download at hp.com/go/upd.

⁵ Paper-handling options must be purchased separately.

Wireless direct printing is standard in the HP Color LaserJet Enterprise flow MFP M880z+ D7P71A model, and may be added as an option to the HP Color LaserJet Enterprise M880z+ A2W76A and M880z A2W75A. Mobile device may require an app or driver. Wireless performance is dependent on physical environment and distance from the printer. For details, see hp.com/go/wirelessprinting.

7 Supports OS X® Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad® (all models), iPhone® (3GS or later), and iPod touch® (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be

^{&#}x27;Supports OS X® Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: Pad® (all models), iPhone® (3GS or later), and iPod touch® (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be connected to the same network as your OS X or iOS device. Wireless performance is dependent on physical environment and distance from the access point. OS X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc.

⁸ HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

⁹ HP Imaging and Printing Security Center must be purchased separately.

Product walkaround

HP Color LaserJet Enterprise flow MFP M880z+ shown:

- 1. Intuitive 20.3 cm (8-inch) HP Easy Select pivoting colour touchscreen control panel
- 2. 200-sheet automatic document feeder with single pass two sided scanning, and HP EveryPage with ultrasonic double-feed detection
- 3. Home button (returns to home screen)
- 4. Plate glass colour scanner handles sizes up to A3
- 5. Easy-access USB port to save and print files directly
- 6. Hardware integration pocket for solution integration
- 7. 500-sheet output bin
- 8. Front door provides convenient access to HP toner cartridges and drums $\,$
- 9. Built-in automatic two-sided printing
- 10. Retractable keyboard for easy, accurate data entry
- 11. 100-sheet multipurpose tray 1 handles heavy custom media up to 220 g/m^2
- 12. Right-side doors provide access to the fuser and duplexer and for clearing jams
- 13. 500-sheet input tray supports media up to size A3
- 14. 3,500-sheet high-capacity input tray supports A4 media
- 15. Access port for optional Kensington-style lock
- 16. HP High-Performance Secure Hard Disk
- 17. HP Jetdirect Gigabit Ethernet print server
- 18. 800 MHz processor, 1.5 GB RAM
- 19. Hi-Speed USB 2.0 port (for connecting third-party devices)
- 20. Hi-Speed USB 2.0 printing port
- 21. Two internal host USB 2.0 type ports for third party solutions
- 22. Foreign interface harness (for connecting external devices)
- 23. RJ-11 fax port





Series at a glance



HP Color LaserJet Enterprise flow M880z Multifunction Printer

- HP Color LaserJet Enterprise flow MFP M880z: print, copy, scan, digital send, fax
- print/copy speed of up to 46 ppm black/colour
- up to 1200 x 1200 dpi (HP FastRes 1200)
- 1.5 GB memory
- 800 MHz processor
- 320 GB Hard Disk with encryption
- 2 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 1 Gigabit Ethernet 10/100/1000T network
- 1 Foreign Interface
- 1 Hardware Integration Pocket
- 2 Internal USB Host
- 100-sheet multi-purpose tray
- 1 x 500-sheet input tray
- 3 x 500-sheet input tray with stand



HP Color LaserJet Enterprise flow M880z+ Multifunction Printer

- As HP Color LaserJet Enterprise flow MFP M880z with 100-sheet multipurpose tray
- 1 x 500-sheet input tray
- 1 x 3500-sheet high capacity input tray with stand



HP Color LaserJet Enterprise flow M880z+ NFC/Wireless Direct MFP Printer

 As HP Color LaserJet Enterprise flow MFP M880z+ with touch-to-print and NFC/Wireless Direct printing

Recommended accessories



HP Color LaserJet Stapler/Stacker

HP Color LaserJet Finishers improve workflow management by upgrading your printer to automatic stapling and sheet stacking. Monitor your printer less frequently with convenient automatic job stapling and sorting in the additional output bin.



A2W83A **HP Color LaserJet Booklet** Maker/Finisher

HP Color Laser let Finishers allow you. to create complex documents with three bins, automatic offset, inline stapling and stacking and booklet making with saddle-stitching and v-folding



J8029A HP Jetdirect 2800w NFC/Wireless **Direct Accessory**

This accessory enables wireless printing with touch-to-print convenience from NFC-capable devices or through a secure peer-to-peer connection from smartphones, tablets, and laptops. 1,2,3



CC383A HP 2-pack 2000-staple Cartridge for booklet maker finisher

HP Staple Cartridge Booklet Maker (2 x 2000 staples) compatibile with HP Color LaserJet CP6015 Printer series and HP Color Laser let CM6030/CM6040 MFP series.



C8091A **HP Staple Cartridge Refill** (5000 staples) for Stapler/Stacker accessories

HP Staple Cartridge Refills give you more for your money and ensure you don't have to worry about frequent cartridge replacement. Fach refill contains 5000 staples.

Ordering information



Accessories A2W80A

A2W83A

CC383A

C8091A

HP Color LaserJet Enterprise flow M880z Multifunction Printer (A2W75A)

HP Color LaserJet Enterprise flow MFP M880z; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 3 x 500-sheet input tray with stand; Fax, Fax cable



HP Color LaserJet Enterprise flow M880z+ Multifunction Printer (A2W76A)

HP Color LaserJet Enterprise flow MFP M880z+; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 1 x 3500-sheet high capacity input tray with stand; Fax, Fax cable



HP Color LaserJet Enterprise flow M880z+ NFC/Wireless Direct MFP Printer (D7P71A)

HP Color LaserJet Enterprise flow MFP M880z+NFC/Wireless Direct; Black, Cyan, Magenta, and Yellow HP Color LaserJet Drums; Black, Cyan, Magenta, and Yellow HP Color LaserJet Toner Cartridges; CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord; HP Jetdirect Gigabit Ethernet Print Server (embedded); Automatic duplexer (built-in); Encrypted Hard Drive; 100-sheet multipurpose tray; 1 x 500-sheet input tray; 1 x 3500-sheet high capacity input tray with stand; Fax, Fax cable; NFC/direct print kit

Accessories, Supplies and Support

HP 2-pack 2000-staple Cartridge for booklet maker

HP Color LaserJet Stapler/Stacker

HP Color LaserJet Booklet Maker/Finisher

HP Staple Cartridge Refill (5000 staples) for

CC487A	HP LaserJet MFP Analog Fax Accessory 5				
CZ999A	HP Color LaserJet Booklet Maker/Finisher with 2/4				
	hole punch				
A2W82A	HP Color LaserJet Stapler/Stacker with 2/4 hole				
	punch				
A7W13A	HP LaserJet Keyboard Overlay				
	Kit-Danish/French-Switzerland/German-				
	Switzerland				
Connecti	vity				
J8029A	HP Jetdirect 2800w NFC/Wireless Direct Accessory				
J8026A	HP Jetdirect 2700w USB Wireless Print Server				
J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print				
	Server				
Supplies					
C1N54A	HP LaserJet C1N54A 110V Maintenance Kit				
	100,000 pages				
C1N58A	HP LaserJet C1N58A 220V Maintenance Kit				
	100,000 pages				

C1P70A	HP LaserJet ADF Roller Replacement Kit Average yield: 100,000 pages		
CF300A	HP 827A Black Original LaserJet Toner Cartridge Average continuous Black Cartridge yield 29,500 standard pages. Declared yield value in accordance with ISO/IEC 19798.		
CF301A	HP 827A Cyan Original LaserJet Toner Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 32,000 standard pages. Declared yield value in accordance with ISO/IEC 19798.		
CF302A	HP 827A Yellow Original Laser Jet Toner Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 32,000 standard pages. Declared yield value in accordance with ISO/IEC 19798.		
CF303A	HP 827A Magenta Original LaserJet Toner Cartridge Average continuous composite Cyan/Yellow/Magenta Cartridge yield 32,000 standard pages. Declared yield value in accordance with ISO/IEC 19798.		
CF358A	HP 828A Black LaserJet Image Drum 30,000 pages		
CF359A	HP 828A Cyan LaserJet Image Drum		

CF364A	HP 828A Yellow LaserJet Image Drum
	30,000 pages
CF365A	HP 828A Magenta LaserJet Image Drum
	30,000 pages
D7H14A	HP LaserJet D7H14A Transfer and Roller Kit
	150,000 pages

Service & support

U8D14E - HP 3 year Next Business Day Color LaserJet M880MFP HW Support

U8D17E - HP 3 year 4 hour 9x5 Color LaserJet M880MFP HW

U8D15E - HP 4 year Next Business Day Color LaserJet M880MFP HW Support

U8D16E - HP 5 year Next Business Day Color LaserJet M880MFP HW Support

U8D38PE - HP 1 year Post-Warranty Next Business Day Color LaserJet M880MFP HW Support

U8D40PE - HP 1 year Post-Warranty 4 hour 9x5 Color LaserJet M880MFP Support

U8D39PE - HP 2 year Post-Warranty Next Business Day Color LaserJet M880MFP HW Support

*(J8029A) HP Jetdirect 2800w NFC/Wireless Direct Accessory and (J8026A) HP Jetdirect 2700w USB Wireless Print Server cannot be installed at the same time

For a complete list of supplies, accessories and services, please refer to http://www.hp.com For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies

30,000 pages

Technical specifications

Print technology	Laser						
Print speed	A4 black: Up to 46 ppm, A4 colour: Up to 46 ppm, A4 duplex: Up to 43 ipm						
Till Speed	A3 black: Up to 22 ppm, A3 colour: Up to 22 ppm						
		As black, up to 22 ppin, as toloud, up to 22 ppin First page out black (Ad): As fast as 11 sec. First page out colour (Ad): As fast as 11 sec					
	rnst page out undex twah, as loads of 11 Sec., risk page out colour (war, as load of 11 Sec.) Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application,						
	driver, and document complexity. 800 MHz						
Processor							
Memory	1.5 GB. Not expandable						
Hard disk	Standard, minimum 320 GB HP I	High-Performance Secure Hard Disk (AES 256 hardware encryp	otion or greater)				
Print	Quality						
	Resolution	Black: Up to 1200 x 1200 dpi, Color: Up to 1200 x 1200 dpi					
	Printer languages	HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation, PDF					
	Typefaces/fonts	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale					
		Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS					
		Emulation available at hp.com/go/laserjetfonts					
	Duty cycle (monthly, A4)	Up to 200,000 pages					
	Recommended monthly page volume	5000 to 25,000					
	Print margins (mm)	Top: 2.1 mm. Left: 2.1 mm. Right: 2.1 mm. Bottom: 2.1 mm					
	Maximum print area	312 x 457.2 mm					
Fax	Modem speed	33.6 kbps					
	Telecom compliance	Fax Telecom: ES 203 021; R&TTE Directive 1999/5/EC (Annex II) with CE Marking (Europe); FCC Part 68; other Telecom approvals as required by individual countries					
	Fax memory	Incoming fax can be stored to disk					
	Fax resolution	Standard: 100 x 100 dpi. Fine: 200 x 200 dpi, 256 levels of grey. Superfine: 300 x 300 dpi, 256 levels of grey					
	Quick dialing	Up to 100 (each can contain 100 numbers)					
Digital sending	File formats	Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Searchable PDF (OCR), HTML (OCR), CSV (OCR);					
		Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A, TEXT (OCR), Unicode TEXT (OCR), RTF (OCR), Searchable PDF (OCR), Search					
	Footures	CSV (OCR); Print from easy access USB: PDF, PS, Print Read Standard: Scan to e-mail; Save-to-Network Folder; Scan to		a LAN Fave Sand to Internet Fave OCD: Local Address Real			
	Features						
		SMTP over SSL. Optional: Optional via HP Digital Sending Software (HP DSS); Send to folder; Send-to-workflow; Send-to-printer; Authentication; Digital fax (send to LAN Internet); OCR; Local Address Book; via HP Embedded Capture; Metadata capture and validation; Data transfer; Scan workflow management					
Scan	Scan Speed (A4)	Up to 70 ppm (black & white), up to 68 ppm (colour); Scan					
Jean.	Type	Flatbed, ADF. Colour scanning:Yes	apara sopies, v,. op to os ipin (black & white), up				
	Scan resolution	Optical: Up to 600 dpi					
	Bit depth	24-bit					
	Grey scale levels	256					
	Scannable area (ADF)	Minimum media size: 147 x 68 mm. Maximum media size:	297 x 432 mm				
Сору	Copy speed	A4 black: Up to 46 cpm, color: Up to 46 cpm					
	Copy resolution	Up to 600 x 600 dpi					
	Multiple copies Reduce/enlarge	Up to 9999 copies 25 to 400%					
Madia bandina			Maight	Cine			
Media handling	Input: Tray 1	Capacity sheets: 100; envelopes: 10	Weight 60 to 220 g/m²	Size A3, A4, A4-R, A5, B5 (JIS), B4 (JIS); RA4, SRA4, RA3,			
	ildy i	sileets. 100, envelopes. 10	00 to 220 g/m	SRA3, A6, B6 (JIS), Dpostcard (JIS); Envelopes: B5, C5,			
				C6. DL			
	Tray 2	sheets: 500	60 to 220 g/m ²	A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4, SRA4			
	Tray 3	A2W75A: sheets: 3 x 500; A2W76A: Tray 3: sheets:	A2W75A: Tray 3, 4, 5: 60 to 220 g/m ² ;	A2W75A: A3, A4, A4-R, A5, B5 (JIS), B4 (JIS), RA4,			
		1500; Tray 4: sheets: 2000; D7P71A: Tray 3: sheets:	A2W76A: Tray 3, 4: 60 to 120 g/m²; D7P71A:	SRA4, 8K (270 x 390), 8K (260 x 368), 8K (273 x			
		1500; Tray 4: sheets: 2000;	Tray 3, 4: 60 to 120 g/m²;	394), 16K (195 x 270), 16K (184 x 260), 16K (197 x			
			-,-,	273), RA3, SRA3; A2W76A: A4-L, LTR-L; D7P71A:			
				275), 1015, 51015, REWYON. 714 E, E111 E, B71 7 IA.			
				A4-L, LTR-L;			
	ADF	sheets: 200 (75 g/m²)	45 to 199 g/m²	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS)			
	Maximum input capacity	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A:	: Up to 4100 sheets (75 g/m² media); D7P71A: Up t	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS)			
	Maximum input capacity Output:	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up	: Up to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS)			
	Maximum input capacity Output: Maximum output capacity:	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpu	: Up to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS)			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard)	: Up to 4100 s-heets (75 g/m² media); D7P71A: Up t to 60 envelopes. Transparencies: Up to 100 sheets ut device.	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media);			
Interface and connectivity	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 He	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard) ost; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100	: Up to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets ut device. OT Network; 1 Foreign Interface; 1 Hardware Integra	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); stion Pocket (HIP); 2 Internal USB Host; 1 Fax			
Interface and connectivity	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: A2W75A: HP Jetdirect	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard) ost; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100: ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdireci	: Up to 4100 sheets (75 g/m² media); D7P71A : Up t to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integra t 2700w USB Wireless Print Server J8026A; HP Jetdii	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP			
interface and connectivity	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard) sst; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect eless Print Server J8021A; HP Jetdirect 2700w USB Wireless	: Up to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets tt device. OUT Network; 1 Foreign Interface; 1 Hardware Integrate t 2700w USB Wireless Print Server J8026A; HP Jetdii rint Server J8026A; HP Jetdii rint Server J8026A; HP Jetdii rint Server J8026A; HP Jetdirect 2800w NFC & Wirele	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Ho Optional: A2W75A: Hy Eduirect Jetdirect ew2500 802.11b/g Wireless Print Server	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard) st; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10C ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect L9706 W USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A	: Up to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets ut device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700 USB Wireless Print Server J8026A; HP Jetdir int Server J8026A; HP Jetdirect 2800w NFC & Wirele V.	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS); o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wire 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Windows 8 (32-bit/64	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard) ost; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100: ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect eless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A; Wireles	EUp to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. 90T Network; 1 Foreign Interface; 1 Hardware Integrat 2700w USB Wireless Print Server J8026A; HP Jetdirict Server J8026A; HP Jetdirect 2800w NFC & Wirele V;	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) to 4100 sheets (75 g/m² media); stion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit),			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit)	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) sst; THi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect eless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80266/ows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mindows Server 2003 (SP1 or higher) (32-bit/64-bit)	LUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets tt device. JOTN Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdiir irint Server J8026A; HP Jetdiirint Server J8026A; HP Jetdii	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax rect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356)	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) st; THi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; THi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; Thi-Speed	Price to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. Description of the device of	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS); o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A : HP ss Direct J8029A; D7P71A : HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print n/go/eprintsoftware); Linux (hplip.net); Novell			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit (support.apple.com/kb/ht4356); (novell.com/pirint); SAP device ty	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) sst; THi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect eless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80266/ows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac 00; Mindows Server 2003 (SP1 or higher) (32-bit/64-bit), Mindows Server 2003 (SP1 or higher) (32-bit/64-bit)	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets it device. DOT Network; 1 Foreign Interface; 1 Hardware Integrat 2700w USB Wireless Print Server J8026A; HP Jetdiritt Server J8026A; HP Jetdiritt Server J8026A; HP Jetdirect 2800w NFC & Wirele X; SY (SP2 or higher) (32-bit/64-bit), Windows Server SIX v10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1 so (hp.com/go/upd); HP ePrint Software Driver (hp.couluntX) (hp.com/go/unix); UNIX® JetDirect (hp.com/go/unix); UNIX® (bp.com/go/unix); UNIX® (bp.com/go/unix	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported			
	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional outpudard) ost; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100: ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect less Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J802A; HP Jetdirect 2700w USB Wireless Print Server J802A; Wireless	: Up to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets tt device. OUT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir rint Server J8026A; HP Jetdirect 2800w NFC & Wirele St SY (SP2 or higher) (32-bit/64-bit), Windows Server IS X v10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For Is (hp.com/go/upl); HP ePrint Software Driver (hp.com/go/upl); UNIX® (hp.com/go/unix); UNIX® JetDirect (hp.com/go/fregion. Select Drivers & Downloads. Enter a product	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware), Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver			
Operating systems compatibility	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ewz500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/pirint); SAP device ty operating systems are available language, Select your Operating	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up up to 3000 sheets (75 g/m² media) with an optional output dard) sst; THi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; euw2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect eless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8025A; HP Jetdirect 2700w USB Wireless Print Server J8026A; hP Jetdirect 32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac O Android (android.com/); Citrix® and Windows Terminal Service ypes (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country.	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets it device. 20 TN etwork; 1 Foreign Interface; 1 Hardware Integrate 2 to 2700 w USB Wireless Print Server J8026A; HP Jetdiirint J8026A; HP	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A : HP ss Direct J8029A; D7P71A : HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print n/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box.			
Operating systems compatibility	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Ho Optional: AZW75A: H) Eddirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit (support-apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) st; T Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; T Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; T Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; T Hi-Speed USB 2.1 Hi-S	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdirist Server J8026A; HP Jetdirist Server J8026A; HP Jetdirist Server J8026A; HP Jetdirect 2800w NFC & Wireles, SP (SP2 or higher) (32-bit/64-bit), Windows Server SX V 10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (hp.com/go/upd); HP ePrint Software Driver (hp.com/go/upd); HP ePrint Software Driver (hp.com/go/region. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD., FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery,	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A : HP ss Direct J8029A; D7P71A : HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print n/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box.			
Operating systems compatibility Supported Network Protocols	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: A2W75A: HP) Jetdirect Jetdirect ew2500 802.11b/g Wire 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint): SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP SLP, TETP, Telnet, IGMPV	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) st; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10C ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A ows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows (1), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Marc Ox Android (android.com/); Citrix® and Windows Terminal Service ypes (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country, system, Under Download, Select Drivers or Firmaware; If no ac tible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS	Price to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP J8026A; H	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4:			
Operating systems compatibility Supported Network Protocols	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bi (support.apple.com/kb/ht4355); (novell.com/jprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard c	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) st; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/10C e. ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect eless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A ows 7 (32-bit/64-bit). Windows USB Wireless Print Server J8026A ows 7 (32-bit/64-bit), Windows USB Wireless Print Server J8026A ows 7 (32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac Own Android Gandroid.com/); Citrix® and Windows Terminal Service ypes (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support, go to hp.com/support. Select your country, system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS 2, BOOTP/DHCR, WINS, IP Direct Mode, WS Print; Other: IPX/SPA iigher), Windows Vista, Windows XP (SP2 or higher),	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdirint Server J8026A; HP Jetdirint Server J8026A; HP Jetdirect 2800w NFC & Wireles & SP (SP2 or higher) (32-bit/64-bit), Windows Server SX V 10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (hp.com/go/upd); HP ePrint Software Driver & DUNIX® (hp.com/go/upd); HP ePrint Software Driver (hp.com/go/upd); HP ePrint Software Driver & DOWNIX® (hp.com/go/upd); HP ePrint Software Drive	A4-L, LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); stion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; 22W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/ge/prints/ftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPSec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 connection (Operating system compatible hardware			
Interface and connectivity Operating systems compatibility Supported Network Protocols Minimum system requirements	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hc Optional: A2W75A: HP) Jetdirect Jetdirect ew2500 802.11b/g Wire 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint): SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP SLP, TETP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or I (64-bit); 200 MB available hard c system requirements see micros	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output ard) ost; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80256 60ws 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac O Android (android.com/); Citrix® and Windows Terminal Service ppes (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country system, Under Download, Select Drivers or Firmaware; If no ac tible (Mac OS v10.2.4 and lacty, SNMPv1/v2c/v3, HTTP, HTTPS 2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SPX igher), Windows Vista, Windows XP Srint; Other: IPX/SPX igher), Windows Vista, Windows XP Srint; Other: IPX/SPX igher), Windows Vista, Windows XPS To 1.5 Lion, OS X 10.8 Moun	Pup to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. OTN Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int Server J8026A; HP Jetdirect 2800w NFC & Wirele X; Sr (Sp2 or higher) (32-bit/64-bit), Windows Server IS X v10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (Inp.com/go/Jupi); HP ePrint Software Driver (Inp.com/go/region. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD. J. FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, K, AppleTalk, NetWare NDS, Bindery, NDPS, IPrint Server 2012 (64-bit), Windows Server 2008; Window ated Universal Serial Bus (USB 1.1 or 2.0), or networ tain Lion; 1 GB of available hard disk space; CD-ROM	A4-L_LTR-L: A3; A4; A5; B4; B5 (JIS); B6 (JIS) to 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NrC & Wireless Direct J80294; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/ge/prints/ftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPSec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 connection (Operating system compatible hardware			
Operating systems compatibility Supported Network Protocols Minimum system requirements	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/fiprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-1P; SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard o system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) st; T.Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100: eve2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80266 wos 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac Oa Android (android.com/); Citrix® and Windows Terminal Service (pse (hp.com/go/sap/driver), SAP Print (hp.com/go/sap/print), at hp.com/support; go to hp.com/support. Select your country system, Under Download, Select Drivers or Firmaware; If no ac tible (Mac OS v10.2.4 and later), SNMPV1/v2c/v3, HTTP, HTTPS 2, BOOTP/DHCR, WINS, IP Direct Mode, WS Print; Other: IPX/SP sligher), Windows Vista, Windows XP (SP2 or higher), Wi	Pup to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. OTN Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int Server J8026A; HP Jetdirect 2800w NFC & Wirele X; Sr (Sp2 or higher) (32-bit/64-bit), Windows Server IS X v10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (Inp.com/go/Jupi); HP ePrint Software Driver (Inp.com/go/region. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD. J. FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, K, AppleTalk, NetWare NDS, Bindery, NDPS, IPrint Server 2012 (64-bit), Windows Server 2008; Window ated Universal Serial Bus (USB 1.1 or 2.0), or networ tain Lion; 1 GB of available hard disk space; CD-ROM	A4-L_LTR-L: A3; A4; A5; B4; B5 (JIS); B6 (JIS) to 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NrC & Wireless Direct J80294; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/ge/prints/ftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPSec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 connection (Operating system compatible hardware			
Operating systems compatibility Supported Network Protocols Minimum system requirements	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/pirint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SPT) or 1 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver;	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media) with an optional output dard) st; T.HSpeed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; T.HSpeed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100 st; T.HSpeed USB 2.1 Device; 1 Gigabit Ethernet 10/100/100 st; T.HSpeed USB 2.1 Device; 1 Gigabit Ethernet 10/100/100 st; T.HSpeed USB 2.1 Device; 1 Gigabit Ethernet 10/100/100 st; T.HSpeed USB 2.1 Device; 1 Device;	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdii rint Server Diver (hp.com/go/Lnix); UNIX* JetDirect (hp.com/go/Lnix)	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A : HP ss Direct J8029A; D7P71A : HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linus (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: ss Server 2003 (SP1 or higher), Windows Server 2008 R2 k connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal			
Operating systems compatibility Supported Network Protocols	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Windows Server 2008 R2 (64-bit (support.apple.com/kb/ht/4356); (novell.com/print); SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Drive; 20.3 cm colour LCD with capaciti	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output ard) st; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026 ws; 7 (32-bit/64-bit), Windows (1), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Windows (1), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac O Android (android.com/); Citrix® and Windows Terminal Service pres (hp.com/go/sap/driver); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country, system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS, 2, BO0TP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SP, iigher), Windows Vista, Windows XP (SP2 or higher), Windows (SP4 No.6) & v10.6, SV v10.7.5, Lion, OS X v10.6 Mountwork connection (Operating system compatible hardware systems Conferent; rotating (adjustable angle) display; illuminated ve touchscreen; rotating (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the	LUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. OTT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int Jet	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); stion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NrC & Wireless Direct J80294; A2W76A : HP ss Direct J80294; D7P71A : HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/ge/prints/ftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPSec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 oc connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output of the season of t	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. OUT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP J8026A; H	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewall; IPv6: DHCPv6, MLDV1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal me menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watts			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b(g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/fiprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-1Ps SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard o system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump?	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output ard) st; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026 ws; 7 (32-bit/64-bit), Windows (1), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Windows (1), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac O Android (android.com/); Citrix® and Windows Terminal Service pres (hp.com/go/sap/driver); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country, system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS, 2, BO0TP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SP, iigher), Windows Vista, Windows XP (SP2 or higher), Windows (SP4 No.6) & v10.6, SV v10.7.5, Lion, OS X v10.6 Mountwork connection (Operating system compatible hardware systems Conferent; rotating (adjustable angle) display; illuminated ve touchscreen; rotating (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the conservation (adjustable angle) display; illuminated very conservation of the	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. OUT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP J8026A; H	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal me menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Windows Server 2008 R2 (64-bit (support.apple.com/kb/ht/4356); (novell.com/print); SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty.	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output ard) st; T. Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J802A; My Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Windows (3); Albertifa-bit), Windows Vista (32-bit/64-bit), Windows (3); Albertifa-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac O Android (android.com/); Citrix® and Windows Terminal Service pses (hp.com/go/sap/driver); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS, 2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SP igher), Windows Vista, Windows XP (SP2 or higher), Windows (Sisk space; CD-ROM or DVD drive, or Internet connection; Dedic. Soft.com), Mac OS x v10.6.8, OS x 10.7.5 Lion, OS x 10.8 Mountwork connection (Operating system compatible hardware system Connection (Operating system compatible hardware system accompatible hardware system accompatible hardware system connection (Operating system compatible hardware system connection (Operating system compatible hardware system connection (Operating system compatible hardware system connection).	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. OUT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP J8026A; H	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal me menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h)	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/jprint): SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IR, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit): 200 MB available hard of system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output of the west of the	Pup to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int Jet int J	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax rect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware), Linux (hplip.net); Novell //jetdirectunix_software). Linux (hplip.net); Novell //jetdirectunix_software) //jetdirectunix_software			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h)	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/jprint): SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IR, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit): 200 MB available hard of system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output ard) st; T. Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J802A; My Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Windows (3); Albertifa-bit), Windows Vista (32-bit/64-bit), Windows (3); Albertifa-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac O Android (android.com/); Citrix® and Windows Terminal Service pses (hp.com/go/sap/driver); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS, 2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SP igher), Windows Vista, Windows XP (SP2 or higher), Windows (Sisk space; CD-ROM or DVD drive, or Internet connection; Dedic. Soft.com), Mac OS x v10.6.8, OS x 10.7.5 Lion, OS x 10.8 Mountwork connection (Operating system compatible hardware system Connection (Operating system compatible hardware system accompatible hardware system accompatible hardware system connection (Operating system compatible hardware system connection (Operating system compatible hardware system connection (Operating system compatible hardware system connection).	Pup to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int Jet int J	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax rect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware), Linux (hplip.net); Novell //jetdirectunix_software). Linux (hplip.net); Novell //jetdirectunix_software) //jetdirectunix_software //jetdirectunix_softw			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/jprint): SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IR, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit): 200 MB available hard of system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output dard) st; T.Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80266/ with 2700w Server 2003 (SP1 or higher) (32-bit/64-bit), Windows Ferrinal Service ppes (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country. system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS 101.2.4 and later), SNMPP1/V2CV3, HTTI HTTPS 2, B00TP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SPX igher), Windows Vista, Windows XP (SP2 or higher), Windows Stisk space; CD-ROM or DVD drive, or Internet connection; Dedic. inflict connection (Departing system connection (Departing system connection (Departing system connection (Departing system Spile) display; illuminated vot Country of the Vision of Carlo (Vision). Mac OS X 10.5 Hz (+/- 2 Hz), 5.5 A. Consumption: tion (TEC): 6.319 kWh/Week. Power requirements are based of the print of the Vision of Carlo (Vision). With Vision (Vision) and Vision	Pup to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int Jet int J	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax rect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware), Linux (hplip.net); Novell //jetdirectunix_software). Linux (hplip.net); Novell //jetdirectunix_software) //jetdirectunix_software			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b(g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356), (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or t) (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 222 (off). Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 1150 Ut of package: 724 x 635 x 150 HP Web Jetadmin; HP Utility (Ma	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output dard) st; T.Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80266/ with 2700w Server 2003 (SP1 or higher) (32-bit/64-bit), Windows Ferrinal Service ppes (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country. system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS 101.2.4 and later), SNMPP1/V2CV3, HTTI HTTPS 2, B00TP/DHCP, WINS, IP Direct Mode, WS Print; Other: IPX/SPX igher), Windows Vista, Windows XP (SP2 or higher), Windows Stisk space; CD-ROM or DVD drive, or Internet connection; Dedic. inflict connection (Departing system connection (Departing system connection (Departing system connection (Departing system Spile) display; illuminated vot Country of the Vision of Carlo (Vision). Mac OS X 10.5 Hz (+/- 2 Hz), 5.5 A. Consumption: tion (TEC): 6.319 kWh/Week. Power requirements are based of the print of the Vision of Carlo (Vision). With Vision (Vision) and Vision	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets to 60 envelopes. Transparencies: Up to 100 sheets to device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdii rint Server J8026A; HP Jetdiirect 2800w NFC & Wirele SX XV10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (hp.com/go/µpl); HP ePrint Software Driver (hp.com/go/µpl); UnIX® (hp.com/go/µnix); UNIX® petDirect (hp.com/go/region. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD in FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, K, AppleTalk, NetWare NDS, Bindery, NDPS, IPrint Server 2012 (64-bit), Windows Server 2008; Window ated Universal Serial Bus (USB 1.1 or 2.0), or networ tain Lion; 1 G8 of available hard disk space; CD-ROM tem requirements see apple.com) It capacitive Home button (for quick return to the Hor 1100 watts (printing), 1100 watts (copying), 80 wat in the country/region where the printer is sold. Do no M758: 173.33 kg; A2W76A: 175.33 kg; D7P71A:	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPSec/Firewall; IPV6: DHCPV6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal me menul; Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printer			
Operating systems compatibility Supported Network Protocols Minimum system requirements	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/pirpit); SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard o system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty. Out of package: A2W75A: 150. HP Web Jetadmin; HP Utility (Ma Identity management: Kerberos Certificate, Pre-Shared Key, and I	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output output of the west	EUp to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdirint Jet Green Jet Green Server (Bp.com URIX® (Bp.com/go/Juhy); HJP ePrint Software Driver (Bp.com URIX® (Bp.com/go/Juhy); HJWB JetDirect (Hp.com/go/region. Select Drivers & Downloads. Enter a product Ceess to the Internet, see the install notes on the CD J. FTP Port 9100, LPD, IPP Secure-IPP, WP Siscovery, K, AppleTalk, NetWare NDS, Bindery, NDPS, iPrint Server 2012 (64-bit), Windows Server 2008; Window ated Universal Serial Bus (USB 1.1 or 2.0), or networ tain Lion; 1 GB of available hard disk space; CD-ROM term requirements see apple.com) Icapacitive Home button (for quick return to the Hor 1100 watts (printing), 1100 watts (copying), 80 wath the country/region where the printer is sold. Do not the country/region where the printer is sold. Do not Plug-in, 802.1X authentication (EAP-PEAR, EAP-ILS, itional HP and 3rd party advanced authentication sold Plug-in, 802.1X authentication (EAP-PEAR, EAP-ILS)	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax etct 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPSec/Firewall; IPV6: DHCPV6, MLDV1, ICMPV6; IPV4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal the menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printer I75.33 kg;			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b(g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356), (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard or system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 222 (off). Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115 Out of package: 72 av 75 x 150 HP Web Jetadmin; HP Utility (Ma Identity management: Kerberos Certificate, Pre-Shared Key, and I Storage Encryption, Encrypted P	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output dard) st; THi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/100; ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J80266 ows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac On Android (android.com/); Citrix® and Windows Terminal Service (1500 com/go/sap/drivers); SAP Print (hp.com/go/sap/print); at hp.com/support; go to hp.com/support. Select your country system, Under Download, Select Drivers or Firmaware; If no actible (Mac OS v10.2.4 and later), SNMPv1/v2c/v3, HTTP, HTTPS 2, BOOTP/DHCR, WINS, IP Direct Mode, WS Print; Other: IPN/SP sigher), Windows Vista, Windows XP (SP2 or higher), Windows Sids, Space; CD-ROM or DVD drive, or Internet connection; Dedic. Oft.com/ Mac OS v v10.6.8, OS x v10.7.5. Lion, OS x v10.8 Mountwork connection (Operating system compatible hardware sys Mac Software Link to Web (Mac Installer); Windows Installer vet touchscreen; rotating (adjustable angle) display; illuminated O1 to 240 VAC (+/- 10%), 50 Hz (+/- 2Hz), 5.5 A. Consumption: Ution (TEC): 6.319 kWh/Week. Power requirements are based on 19 mm; Packaged: 856 x 790 x 1567 mm 5 kg; AZW76A: 152.9 kg; D7P71A: 152.9 kg; ; Packaged: A21 challed to the proposition of Secondary of the Validated cryptographic libraries from 10 secon	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdii rint Server J8026A; HP Jetdiirect 2800w NFC & Wirele St X V10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (hp.com/go/µpl); HP ePrint Software Driver (hp.com/go/µpl); UnIX® (hp.com/go/µnix); UNIX® petDirect (hp.com/go/region. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD in FTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, K, AppleTalk, NetWare NDS, Bindery, NDPS, IPrint Server 2012 (64-bit), Windows Server 2008; Window ated Universal Serial Bus (USB 1.1 or 2.0), or networ tait inion; 1 G6 of available hard disk space; CD-ROM tem requirements see apple.com) It capacitive Home button (for quick return to the Hor 1100 watts (printing), 1100 watts (copying), 80 wat in the country/region where the printer is sold. Do not the country/region where the printer is sold. Do not the country of the printer of the printer is sold. Do not the country of the printer is sold. Do not the country of the printer is sold. Do not the printer is sold. Do no	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax etct 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal me menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printer I75.33 kg;			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Ho Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Windows 8 (32-bit/64-bit), Windows Server 2008 R2 (64-bit (support.apple.com/kb/ht/356); (novell.com/print): SAP device to operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 16 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 22 (off). Typical Electricity Consump and void the product warranty. Out of package: A2W75A: 150.0 HP Web Jetadmin; HP Utility (Ma Identity management: Kerberos Certificate, Pre-Shared Key, and I Storage Encryption, Encrypted P disablement, hardware integrated	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). When the speed use 2. The speed use 2. Device; 1 Gigabit Ethernet 10/100/100; ew.2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J802A; My Side 12-bit/64-bit), Windows 10; Windows 10; Windows Vista (32-bit/64-bit), Windows 10; Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Windows 10; Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Windows 10; Windows Vista, Windows XP (SP2 or higher), Windows 10; Windows Vista, Windows XP (SP2 or higher), Windows 10; Wind	Up to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP J8026A;	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 k connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printe 175.33 kg; utions (e.g., badge readers); Network: IPsec/firewall with , SNMPv3, HTTPS, Certificates, Access Control List; Data: oted Credentials; Device: Security lock slot, USB port			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/jprint): SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard of system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty. Out of package: A2W75A: 150.1 HP Web Jetadmin; HP Utility (Ma Identity management: Kerberos Certificate, Pre-Shared Key, and I Storage Encryption, Encrypted P disablement, hardware integrati	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output of the west of the	Up to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP J8026A;	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 k connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal the menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printer 175.33 kg; utions (e.g., badge readers); Network: IPsec/firewall with , SNMPv3, HTTPS, Certificates, Access Control List; Data: oted Credentials; Device: Security lock slot, USB port			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wire 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IR SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 20 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 222 (off), Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115 Out of package: 704 x 635 x 115 Und fpackage: Reversor Certificate, Pre-Shared Key, and Storage Encryption, Encrypted P disablement, hardware integrati Operating temperature: 15 to 36 35°C. Storage humidity: 10 to 9 35°C. Storage humidity: 10 to 9	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output and the state of the state	Up to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP J8026A;	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 k connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printe 175.33 kg; utions (e.g., badge readers); Network: IPsec/firewall with , SNMPv3, HTTPS, Certificates, Access Control List; Data: oted Credentials; Device: Security lock slot, USB port			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wire 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IR SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 20 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 222 (off), Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115 Out of package: 704 x 635 x 115 Und fpackage: Reversor Certificate, Pre-Shared Key, and Storage Encryption, Encrypted P disablement, hardware integrati Operating temperature: 15 to 36 35°C. Storage humidity: 10 to 9 35°C. Storage humidity: 10 to 9	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output of the west of the	Up to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP Jetdir int J8026A; HP J8026A;	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ution Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFc & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver hat came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 k connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printe 175.33 kg; utions (e.g., badge readers); Network: IPsec/firewall with , SNMPv3, HTTPS, Certificates, Access Control List; Data: oted Credentials; Device: Security lock slot, USB port			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b(g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-Hg. SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or h (64-bit); 200 MB available hard of system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 22 (off). Typical Electricity Consumpand void the product warranty. Out of package: 704 x 635 x 115 Out of package: 74 x 635 x 115 Out of package: 74 y 635 x 115 Out of package: 74 y 635 x 115 Out of package: 74 y 635 x 115 Out of package: 15 y 635 x 115 Out of package: 15 y 635 x 115 Out of package: 16 y 635 x 115 Out of package: 17 y 635 x 115 Out of package: 17 y 635 x 115 Out of package: 17 y 635 x 115 Out of package: 18 y 635 x 115 Out o	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). With an optional output and the state of the state	EUp to 4100 sheets (75 g/m² media); D7P71A: Up to 60 envelopes. Transparencies: Up to 100 sheets to 60 envelopes. Transparencies: Up to 100 sheets to the device. DOTN Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdii rint Server J8026A; HP Jetdii rint Server J8026A; HP Jetdii rint Server J8026A; HP Jetdirect 2800w NFC & Wirele S. X SY (SP2 or higher) (32-bit/64-bit), Windows Server JS X V10.6.8, v10.7.5 Lion, v10.8 Mountain Lion. For 1s (hp.com/go/µpl); HP ePrint Software Driver (hp.com/go/µpl); HP ePrint Software Driver (hp.com/go/npl); UniX° (hp.com/go/unix); UniX° petDirect (hp.com/go/region. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD., FTP, Port 9100, LPP, Secure-IPP, WS Discovery, K, AppleTalk, NetWare NDS, Bindery, NDPS, IPrint Server 2012 (64-bit), Windows Server 2008; Window ated Universal Serial Bus (USB 1.1 or 2.0), or networ tain Lion; 1 Ge of available hard disk space; CD-ROM tem requirements see apple.com) It capacitive Home button (for quick return to the Hor 1100 watts (printing), 1100 watts (copying), 80 wat in the country/region where the printer is sold. Do no 1100 watts (printing), 1100 watts (copying), 80 wat in the country/region where the printer is sold. Do no 1100 watts (printing), 1100 watts (Copying), 80 wat in the Country/region where the printer is sold. Do no 1100 watts (printing), 1100 watts (Copying), 80 wat in the Country/region where the printer is sold. Do no 1100 watts (Copying), 80 wath the HP and 3rd party advanced authentication sole Plug-in, 802.1X authentication (EAP-PEAP, EAP-TLS, m Microsoft), Secure Erase, SSL/TLS (HTTPS), Encry attiting humidity: 10 to 80% RH. Operating humidity re	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); attion Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: ss Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal ne menul); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printe 175.33 kg; utions (e.g., badge readers); Network: IPsec/firewall with , SNMPv3, HTTPS, Certificates, Access Control List; Data: toted Credentials; Device: Security lock slot, USB port commended: 10 to 80% RH . Storage temperature: 0 to			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b/g wire 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IP, SLP, TETP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or 1 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off), Typical Electricity Consump and void the product warranty. Out of package: R2W75A: 150.1 HP Web Jetadmin; HP Utility (Ma Identity management: Kerberos Certificate, Pre-Shared Key, and I Storage Encryption, Encrypted P disablement, hardware integrati Operating temperature: 15 to 3 35°C. Storage humidity: 10 to 9 Acoustic Power Emissions: 7.0 B CISPR 22:2008 / EN 55022:2010 required by individual countries.	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which is the sheet of the sh	Pup to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int Server J8026A; HP Perint Software Driver (hp.com/go/nrigion. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD J674A; HP J8026A;	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HiP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal one menul; Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printe 175.33 kg; attions (e.g., badge readers); Network: IPsec/firewall with 1, SNMPv3, HTTPS, Certificates, Access Control List; Data: oted Credentials; Device: Security lock slot, USB port commended: 10 to 80% RH. Storage temperature: 0 to			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hir-Speed USB 2.0 Hc Optional: A2W75A: HP Jetdirect Jetdirect ew2500 802.11b(g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit) (support.apple.com/kb/ht4356); (novell.com/iprint); SAP device ty operating systems are available language, Select your Operating IPv4/IPv6: Apple Bonjour Compa Auto-IPs SLP, TFTP, Telnet, IGMPV Windows 8, Windows 7 (SP1 or h (64-bit); 200 MB available hard of system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage; 22 (off). Typical Electricity Consumpand void the product warranty. Out of package: 704 x 635 x 115 Out of package: 74 x 635 x 115 Out of package: 15 y 15 x	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output dard) on the state of the	Pup to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrate 2700w USB Wireless Print Server J8026A; HP Jetdir int Server J8026A; HP Perint Software Driver (hp.com/go/nrigion. Select Drivers & Downloads. Enter a product cess to the Internet, see the install notes on the CD J674A; HP J8026A;	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax ect 2800w NFC & Wireless Direct J8029A; A2W76A: HP ss Direct J8029A; D7P71A: HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 c connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal he menul; Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watt t convert operating voltages. This will damage the printer 175.33 kg; attions (e.g., badge readers); Network: IPsec/firewall with 1, SNMPv3, HTTPS, Certificates, Access Control List; Data: oted Credentials; Device: Security lock slot, USB port commended: 10 to 80% RH. Storage temperature: 0 to			
Operating systems compatibility Supported Network Protocols Minimum system requirements Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	Maximum input capacity Output: Maximum output capacity: Duplex printing: Automatic (stan Standard: 2 Hi-Speed USB 2.0 Hd Optional: AZW75A: HP Jetdirect Jetdirect ew2500 802.11b/g Wir 802.11b/g Wireless Print Server Windows 8 (32-bit/64-bit), Wind Windows 8 (32-bit/64-bit), Wind Windows Server 2008 R2 (64-bit (support.apple.com/kb/ht-4356); (novell.com/print); SAP device ty operating systems are available language, Select your Operating IPw4/IPw6: Apple Bonjour Compa Auto-IP, SLP, TFTP, Telnet, IGMPv Windows 8, Windows 7 (SP1 or 16 (64-bit); 200 MB available hard c system requirements see micros Serial Bus (USB 1.1 or 2.0), or ne HP PCL 6 Discrete Printer Driver; 20.3 cm colour LCD with capaciti Requirements: Input Voltage: 22 (off). Typical Electricity Consump and void the product warranty. Out of package: 704 x 635 x 115 Out of package: 704 x 635 x 115 Out of package: AZW75A: 150.1 HP Web Jetadmin; HP Utility (Ma Identity management: Kerberos Certificate, Pre-Shared Key, and I Storage Encryption, Encrypted P disablement, hardware integratic Operating temperature: 15 to 30 35°C. Storage humidity: 10 to 9 Acoustic Power Emissions: 7.08 CISPR 22:2008 / EN 55022:2010 required by individual countries. (Class 1 Laser/LED Product); 65 i	A2W75A: Up to 2100 sheets (75 g/m² media); A2W76A: Sheets: Up to 500 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Envelopes: Up Up to 3000 sheets (75 g/m² media). Which an optional output dard) on the state of the	Up to 4100 sheets (75 g/m² media); D7P71A : Up to 60 envelopes. Transparencies: Up to 100 sheets at device. DOT Network; 1 Foreign Interface; 1 Hardware Integrit 2700w USB Wireless Print Server J8026A; HP Jetdirint J8026A; HP	A4-L_LTR-L; A3; A4; A5; B4; B5 (JIS); B6 (JIS) o 4100 sheets (75 g/m² media); ation Pocket (HIP); 2 Internal USB Host; 1 Fax etct 2800w NFC & Wireless Direct J8029A; A2W76A : HP ss Direct J8029A; D7P71A : HP Jetdirect ew2500 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), he latest operating system support see: Air Print m/go/eprintsoftware); Linux (hplip.net); Novell //jetdirectunix_software). Latest drivers for supported name/number. Select your product, Select your Driver that came in the printer box. IPsec/Firewalt; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: vs Server 2003 (SP1 or higher), Windows Server 2008 R2 k connection (Operating system compatible hardware or DVD drive, or Internet connection; Dedicated Universal he menu); Easy Access USB; Hardware Integration Pocket ts (ready), 8.0 watts (sleep), 1.2 watt (auto-off), 0.4 watts t convert operating voltages. This will damage the printer 175.33 kg; ations (e.g., badge readers); Network: IPsec/firewall with 1, SNMPv3, HTTPS, Certificates, Access Control List; Data: toted Credentials; Device: Security lock slot, USB port commended: 10 to 80% RH . Storage temperature: 0 to			



